



HP Series 7 Pro 34 inch WQHD Conferencing Monitor - 734pm

Model: 8K157UT

Manufacturer: HEWLETT-PACKARD

EAN: 198415143440

Product Code: 377585

R20,166

Bundled software: HP Display Center HP Client Management Script Library | Certification: BIS BSMI
CB CCC CE CECP CEL EAC FCC ISO 9241-307 KC KCC NOM PSB RCM SEPA TUV-S UL/CSA VCCI WEEE
ISC Low blue light WW application ICE UAE GS Ukraine EE Belarus EE Korea MEPS CEL Grade 2 |
Manufacturer warranty: HP three-year limited warranty | DisplayPort out version: 1.4 | Compliance
certificates: Federal Communications Commission (FCC) | Compliance certificates: BIS | Compliance
certificates: CE | Compliance certificates: CECP | DisplayPort out quantity: 1 | General Product Safety
Regulation (GPSR) URL: https://kaas.hpcloud.hp.com/pdf-public/pdf_11069394_en-US-1.pdf |
Compliance certificates: BSMI | Compliance certificates: CCC | Compliance certificates: CB |
Compliance certificates: EAC | European Product Registry for Energy Labelling (EPREL) code:
1894961 | Colour gamut standard: DCI-P3 | Response time measurement type: GTG (Gray to Gray) |
Colour gamut standard: sRGB | Remotely operated: Yes | USB Power Delivery (USB PD): Yes | USB
Type-C DisplayPort Alternate Mode: Yes | Fast charging: Yes | High Dynamic Range (HDR)
technology: DisplayHDR 400 | Detachable stand: Yes | USB Type-C downstream ports quantity: 1 |
High Dynamic Range (HDR) supported: Yes | Energy efficiency scale: A to G | sRGB coverage

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices
may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or
typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(typical): 100% | Anti-glare screen: Yes | USB Power Delivery up to: 100 W | VESA Adaptive Sync support: Yes | Screen curvature rating: 1900R | VESA mounting: Yes | Number of USB Type-C upstream ports quantity: 1 | Depth (without stand): 120.2 mm | Feet colour: Black | Feet colour: Silver | Built-in KVM switch: Yes | Panel mounting interface: 100 x 100 mm | Energy consumption (HDR) per 1000 hours: 68 kWh | UNSPSC-code: 43211902 | Energy efficiency class (SDR): G | Backlight type: Edge LED | Power consumption (standby): 0.5 W | Non-operating altitude: 0 - 12192 m | AMD FreeSync type: FreeSync Premium | Microphone in: Yes | Power supply type: Internal | Touchscreen: No | Low Blue Light technology: Yes | Haze rate: 25% | Number of speakers: 4 | Cables included: AC | Weight (with stand): 11.3 kg | Market positioning: Business | AMD FreeSync: Yes | Cables included: Thunderbolt | Height: 364.1 mm | Cables included: USB Type-C to USB Type-A | Height adjustment: Yes | Energy consumption (SDR) per 1000 hours: 32.5 kWh | Height (without stand): 364.1 mm | Vertical scan range: 30 - 120 Hz | HP segment: Business | Surface hardness: 3H | Megapixel (approx.): 5 MP | On Screen Display (OSD): Yes | Cables included: DisplayPort | Package height: 485 mm | Pixel density: 109 ppi | Viewable size, horizontal: 80 cm | Sustainability certificates: EPEAT | Sustainability certificates: TCO10 | Sustainability certificates: ENERGY STAR | Sustainability certificates: TCO | Built-in speaker(s): Yes | Picture-in-Picture: Yes | Sustainability certificates: EPEAT Climate + | Maximum refresh rate: 120 Hz | Package depth: 226 mm | Cables included: HDMI | Warranty card: Yes | RMS rated power: 12 W | Tilt adjustment: Yes | Ethernet LAN: Yes | Display diagonal (metric): 86.4 cm | Panel type: IPS Black | Energy efficiency class (HDR): G | HDMI version: 2.0 | Depth: 120.2 mm | Weight (without stand): 8.78 kg | Width (without stand): 813.8 mm | Width: 813.8 mm | Power consumption (typical): 51 W | Audio decoders: DTS Virtual:X | Flicker-free technology: Yes | Colour gamut: 100% | Colour depth: 8 bit | USB Type-A downstream ports quantity: 5 | Viewable size, vertical: 33.5 cm | Built-in camera: Yes | Thunderbolt 4 ports quantity: 2 | Horizontal scan range: 30 - 190 kHz | Display brightness: 400 cd/m² | USB hub version: 3.2 Gen 2 (3.1 Gen 2) | Sustainability compliance: Yes | HDMI: Yes | HDMI ports quantity: 1 | Swivelling: Yes | Contrast ratio (typical): 2000:1 | Built-in USB hub: Yes | Display technology: LCD | Adjustable height (max): 15 cm | Infrared (IR) sensor: Yes | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Viewing angle, horizontal: 178° | Operating relative humidity (H-H): 20 - 80% | Display diagonal: 86.4 cm (34") | NVIDIA G-SYNC: No | Native aspect ratio: 21:9 | Operating altitude: 0 - 5000 m | Product colour: Black | AC input voltage: 100 - 240 V | HD type: Wide Quad HD | Weight: 11.3 kg | Depth (with stand): 266.9 mm | Quick start guide: Yes | Viewing angle, vertical: 178° | DisplayPorts quantity: 1 | Display resolution: 3440 x 1440 pixels | AC input frequency: 50/60 Hz | Operating

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

temperature (T-T): 5 - 35 °C | LED backlight: Yes | Ethernet LAN (RJ-45) ports: 1 | Height (with stand): 547.4 mm | Response time: 5 ms | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | DisplayPort version: 1.4 | Width (with stand): 813.8 mm | Supported graphics resolutions: 1600 x 900 | Supported graphics resolutions: 1280 x 720 (HD 720) | Supported graphics resolutions: 1600 x 1200 (UXGA) | Supported graphics resolutions: 720 x 400 | Power consumption (off): 0.3 W | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 1280 x 1024 (SXGA) | Display surface: Matt | Tilt angle range: -5 - 20° | Built-in microphone: Yes | Display brightness (typical): 400 cd/m² | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | HDCP: Yes | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 1440 x 900 (WXGA+) | Supported graphics resolutions: 3440 x 1440 | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1920 x 1200 (WUXGA) | Package type: Box | Aspect ratio: 21:9 | Screen shape: Curved | Cable lock slot: Yes | Package weight: 17.4 kg | Storage relative humidity (H-H): 20 - 80% | Package width: 952 mm | Power consumption (max): 310 W | Pixel pitch: 0.23 x 0.23 mm | Display number of colours: 16.7 million colours

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950