



TP-Link 9-Port 10/100Mbps Desktop Switch with 8-Port PoE+



Model: TL-SF1009P

Manufacturer: TP-LINK

EAN: 6935364052966

Product Code: 377663

R1,410

Certification: FCC, CE, RoHS | Package weight: 980 g | AC input voltage: 220 V | Package width: 223 mm | Input current: 1.31 A | LED indicators: Power | Harmonized System (HS) code: 85176990 | Storage temperature (T-T): -40 - 70 °C | Total Power over Ethernet (PoE) budget: 65 W | Copper ethernet cabling technology: 10BASE-T | LED indicators: Activity | Power source: DC/PoE | Operating temperature (T-T): 0 - 40 °C | LED indicators: PoE | Switching capacity: 1.6 Gbit/s | Package depth: 280 mm | Operating relative humidity (H-H): 10 - 90% | LED indicators: Link | User guide: Yes | AC input frequency: 50 Hz | Rack mounting: No | Package height: 68 mm | Power consumption (max): 77.08 W | Storage relative humidity (H-H): 5 - 90% | Width: 171 mm | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3af | Height: 27 mm | Power over Ethernet (PoE) power per port: 30 W | Networking standards: IEEE 802.3i | Copper ethernet cabling technology: 100BASE-TX | Networking standards: IEEE 802.3at | Product colour: Black | Power over Ethernet (PoE): Yes | Power supply included: No | Auto MDI/MDI-X: Yes | Housing material: Metal | Package type: Box | AC adapter

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

included: Yes | Networking standards: IEEE 802.3u | Depth: 98 mm | Store-and-forward: Yes | Half duplex: Yes | Full duplex: Yes | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Power connector: DC-in jack | Forwarding rate: 1.3392 Mpps | Heat dissipation: 262.84 BTU/h | Wall mountable: Yes | Cable types supported: Cat3 | Cable types supported: Cat5 | Cable types supported: Cat5e | Basic switching RJ-45 Ethernet ports quantity: 9 | Switch type: Unmanaged | Power over Ethernet plus (PoE+) ports quantity: 8 | Auto-negotiation: Yes | MAC address auto-learning supported: Yes | MAC address auto-aging supported: Yes | Sustainability compliance: Yes | Cable types supported: Cat4 | Fanless: Yes | Stackable: No | MAC address table: 2000 entries | DC input voltage: 53.5 V | Fast Ethernet (copper) ports quantity: 9 | Flow control support: Yes | 10G support: No | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | Warnings: Ensure the unit is adequately ventilated during operation.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950