

TP-Link Omada Gigabit VPN Router



Model: TL-ER605

Manufacturer: TP-LINK

EAN: 1210002611206

Product Code: 377846

R1,381

NAT functionality: One-to-One NAT5 Multi-Net NAT Virtual Server Port Triggering5 NAT-DMZ
FTP/H.323/SIP/IPSec/PPTP ALG, UPnP | Certification: CE, FCC, RoHS | SFP WAN: No | Firewall: Yes |
Gigabit Ethernet (copper) ports quantity: 4 | 3G/4G USB modem compatibility: Yes | SIM card slot: No
| ICMP attack prevention: Yes | Universal Plug and Play (UPnP): Yes | VPN tunnels quantity: 20 | DMZ
support: Yes | DHCP server: Yes | ARP attack prevention: Yes | VLAN support: Yes | URL filtering: Yes |
System event log: Yes | Harmonized System (HS) code: 85176990 | DoS attack prevention: Yes |
Policy-based routing: Yes | Access Control List (ACL): Yes | DSL WAN: No | Static route: Yes | Ethernet
LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 10 | Mac operating systems supported: MacOS
| Product colour: Black | Input current: 1 A | Operating relative humidity (H-H): 10 - 90% | Operating
temperature (T-T): 0 - 40 °C | LED indicators: Power | Ethernet LAN (RJ-45) ports: 4 | LED indicators:
WAN | LED indicators: Status | Storage temperature (T-T): -40 - 70 °C | Windows operating systems
supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Reset button: Yes
| Windows operating systems supported: Windows 98SE | AC adapter included: Yes | Cables included:
LAN (RJ-45) | Windows operating systems supported: Windows 8 | Windows operating systems
supported: Windows XP | DC-in jack: Yes | Windows operating systems supported: Windows 7 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ethernet LAN data rates: 1000 | Power source type: DC | LED indicators: LAN | Ethernet WAN: Yes | Windows operating systems supported: Windows 10 | Security algorithms: SIPS | Networking standards: IEEE 802.3u | Storage relative humidity (H-H): 5 - 90% | Web-based management: Yes | Security algorithms: FTPES | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Network address translation (NAT): Yes | Output current: 1 A | Ethernet interface type: Gigabit Ethernet | Height: 25 mm | Quick installation guide: Yes | Internal memory: 256 MB | Depth: 101 mm | Flash memory: 128 MB | Cabling technology: 10/100/1000Base-T(X) | Linux operating systems supported: Yes | Width: 158 mm | Output voltage: 12 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950