



TP-Link 9-Port 10/100Mbps Desktop Switch with 8-Port PoE+



Model: TL-SF1009P

Manufacturer: TP-LINK

EAN: 1210002616393

Product Code: 377887

R1,645

Certification: FCC, CE, RoHS | Cable types supported: Cat4 | Sustainability compliance: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Half duplex: Yes | Power over Ethernet (PoE): Yes | Forwarding rate: 1.3392 Mpps | Switching capacity: 1.6 Gbit/s | Power connector: DC-in jack | Power over Ethernet plus (PoE+) ports quantity: 8 | Power consumption (max): 77.08 W | Fast Ethernet (copper) ports quantity: 9 | Cable types supported: Cat3 | Basic switching RJ-45 Ethernet ports type: Fast Ethernet (10/100) | Storage relative humidity (H-H): 5 - 90% | DC input voltage: 53.5 V | Housing material: Metal | Operating temperature (T-T): 0 - 40 °C | Total Power over Ethernet (PoE) budget: 65 W | MAC address auto-aging supported: Yes | MAC address auto-learning supported: Yes | Power over Ethernet (PoE) power per port: 30 W | Fanless: Yes | Power source: DC/PoE | 10G support: No | Wall mountable: Yes | Auto-negotiation: Yes | Stackable: No | Full duplex: Yes | Rack mounting: No | MAC address table: 2000 entries | Height: 27 mm | Package type: Box | Auto MDI/MDI-X: Yes | Copper ethernet cabling technology: 10BASE-T | Networking standards: IEEE 802.3at | Width: 171

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

mm | Basic switching RJ-45 Ethernet ports quantity: 9 | Depth: 98 mm | Copper ethernet cabling technology: 100BASE-TX | Package width: 223 mm | Flow control support: Yes | Store-and-forward: Yes | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3x | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3u | Power supply included: No | Package height: 68 mm | Package weight: 980 g | Harmonized System (HS) code: 85176990 | Product colour: Black | AC adapter included: Yes | Package depth: 280 mm | User guide: Yes | Storage temperature (T-T): -40 - 70 °C | Networking standards: IEEE 802.3af | AC input frequency: 50 Hz | Heat dissipation: 262.84 BTU/h | LED indicators: Activity | LED indicators: Link | Switch type: Unmanaged | Input current: 1.31 A | AC input voltage: 220 V | LED indicators: PoE | LED indicators: Power | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950