



Mercusys MB520-5G Router



Model: MB520-5G

Manufacturer: MERCUSYS

EAN: 6957939004026

Product Code: 377936

R4,178

Reset button: Yes | Ethernet LAN (RJ-45) ports: 2 | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Width: 190 mm | Ethernet LAN data rates: 100 Mbit/s | Ethernet LAN data rates: 1000 Mbit/s | Ethernet WAN: Yes | Ethernet LAN data rates: 10 | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Output voltage: 12 V | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 4 (802.11n) | Security algorithms: WPA3-SAE | Security algorithms: WPA2-PSK | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Quick installation guide: Yes | Product colour: White | Storage temperature (T-T): -40 - 60 °C | Warnings: Do not expose the device to water or moisture. | Warnings: Do not dismantle the unit yourself, there is a risk of electric shock. | Warnings: Do not expose the device to extreme temperatures. | Antenna design: Internal | SIM card slot: Yes | Depth: 130 mm | Ethernet LAN: Yes | WPS push button: Yes | Output current: 2 A | 4G bands supported: 700 | 4G bands supported: 2300 MHz | 4G bands supported: 2100 | 4G bands supported: 800 | 4G bands supported: 900 | RJ-11 ports quantity: 1 | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 2500 | 4G bands supported: 1800 | Universal Plug and Play (UPnP): Yes | 4G bands supported: 3700 MHz | 4G bands supported: 3500 | Power supply included: Yes | Indication light: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| SIM card type: NanoSIM | Mobile network generation: 5G | UMTS bands supported: 850 | UMTS bands supported: 2100 MHz | Wi-Fi band: 2,4 GHz, 5 GHz | 3G standards: UMTS | 3G standards: HSPA+ | Port-based Network Access Control (PNAC): Yes | Firewall: Yes | Dynamic DNS (DDNS): Yes | WAN connection type: RJ-45 | DHCP server: Yes | Height: 69.7 mm | UMTS bands supported: 900 | VoIP protocols: IPv4, IPv6 | 4G standard: LTE-TDD & LTE-FDD | DMZ support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950