



TP-Link Omada 48-Port Gigabit L2+ Managed Switch with 4 SFP Slots



Model: TL-SG3452

Manufacturer: TP-LINK

EAN: 1210002611923

Product Code: 378032

R8,591

Certification: CE, FCC, RoHS | Web-based management: Yes | MAC address filtering: Yes | Networking standards: IEEE 802.1s | Port mirroring: Yes | MAC address table: 16000 entries | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Jumbo frames support: Yes | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1w | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | DHCP features: DHCP server | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): 10 - 90% | Package weight: 4.26 kg | Cables included: AC | SFP module slots quantity: 4 | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1D | Networking standards: IEEE 802.3z | Ethernet LAN data rates: 10,100,1000 Mbit/s | Quick start guide: Yes | Switching capacity: 104 Gbit/s | Package width: 528 mm | DHCP features: DHCP snooping | Switch layer: L2 | DHCP features: DHCPv6 snooping | AC input voltage: 100 - 240 V | Flash memory: 32 MB | IGMP snooping: Yes | Harmonized System (HS) code: 85176990 | Rack mounting: Yes | Power over Ethernet (PoE): No | Width: 440 mm | AC input

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

frequency: 50/60 Hz | Depth: 220 mm | Access Control List (ACL): Yes | Package height: 100 mm | Basic switching RJ-45 Ethernet ports quantity: 48 | Height: 44 mm | DHCP features: DHCP client | DHCP features: DHCP relay | Heat dissipation: 118.94 BTU/h | Multicast support: Yes | Networking standards: IEEE 802.3i | Power supply included: Yes | Switch type: Managed | Form factor: 1U | Power consumption (max): 34.86 W | Power source: AC | VLAN support: Yes | Number of VLANs: 4000 | Product colour: Black | Internal memory: 256 MB | 10G support: No | Package depth: 336 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Policy-based routing: Yes | IPv6 routes: 48 | Console port: RJ-45/Micro-USB | Cloud-managed: Yes | IPv4 & IPv6 features: IPv6 traceroute | MIB support: Yes | Virtual LAN features: Voice VLAN | GARP VLAN Registration Protocol (GVRP): Yes | System event log: Yes | IPv4 routes: 48 | IP-MAC-Port binding: Yes | Forwarding rate: 77.4 Mpps | IPv4 & IPv6 features: IPv6 Telnet | BPDU filtering/protection: Yes | Virtual LAN features: Tagged VLAN | IPv4 & IPv6 features: IPv4/IPv6 access-control list (ACL) | Authentication type: AAA, RADIUS, TACACS+ | IP routing: Yes | IPv4 & IPv6 features: IPv6 ping | ARP inspection: Yes | Head-of-line (HOL) blocking: Yes | Virtual LAN features: Protocol-based VLAN | Fanless: Yes | Management protocols: SNMPv1/v2c/v3, SNTTP | Virtual LAN features: Port-based VLAN | Configuring Location Settings (CLI): Yes | Virtual LAN features: Private VLAN | Loop protection: Yes | Spanning tree protocol: Yes | Static route: Yes | Broadcast storm control: Yes | Multicast Listener Discovery (MLD) snooping: Y | Store-and-forward: Yes | Link aggregation: Yes | Gigabit Ethernet (copper) ports quantity: 48 | Jumbo frames: 9000 | Authentication: MAC-based authentication, Port-based authentication | Rack mount kit: Yes | SSH/SSL support: Yes | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950