



ASUS 90IG0A30-MO9C00 wireless router 2.5 Gigabit Ethernet Tri- band (2.4 GHz 5 GHz 6 GHz) Black

Model: TUF-BE9400

Manufacturer: ASUS

EAN: 4711387931851

Product Code: 378039

R3,932

VPN support: nstant Guard VPN Client L2TP VPN Client Open VPN VPN Client PPTP VPN Client WireGuard VPN Server IPSec VPN Server Open VPN VPN Server PPTP VPN Server WireGuard VPN Fusion Support Surfshark Support Nord VPN | Port triggering: Yes | Output current: 2.5 A | DMZ support: Yes | WPS push button: Yes | Firewall security: Maximum Firewall Keyword Filter : 64 • Maximum Firewall Network Service Filter : 32 • Maximum Firewall URL Filter : 64 | Firewall: Yes | WLAN data transfer rate (first band): 688 Mbit/s | System event log: Yes | Wi-Fi band: Tri-band (2.4 GHz / 5 GHz / 6 GHz) | Warranty card: Yes | Dynamic DNS (DDNS): Yes | WLAN data transfer rate (second band): 2882 Mbit/s | Flash memory: 256 MB | DHCP server: Yes | Parental control: Yes | Port

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

forwarding: Yes | USB port: Yes | Depth: 179 mm | WLAN data transfer rate (third band): 5764 Mbit/s | Built-in FTP server: Yes | Internal memory: 1000 MB | On/off switch: Yes | Ethernet LAN: Yes | SIM card slot: No | WAN connection type: RJ-45 | Bandwidth control: Yes | Built-in processor: Yes | Height: 191 mm | 3G/4G USB modem compatibility: Yes | MU-MIMO technology: Yes | Product type: Tabletop router | Media server: Yes | Antenna design: External | Support Samba (storage): Yes | Ethernet WAN: Yes | Modulation: 4096-QAM | AC adapter included: Yes | Product colour: Black | Package type: Box | Weight: 764 g | Wi-Fi standards: 802.11b | Package depth: 236 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Modulation: OFDMA | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 7 (802.11be) | Quick start guide: Yes | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 6E (802.11ax) | Processor frequency: 1500 MHz | Quality of Service (QoS) support: Yes | Ethernet LAN interface type: 2.5 Gigabit Ethernet | Antennas quantity: 6 | Package height: 82 mm | Top Wi-Fi standard: Wi-Fi 7 (802.11be) | Package weight: 1.25 kg | Output voltage: 12 V | Processor cores: 4 | Package width: 442 mm | Ethernet LAN (RJ-45) ports: 4 | Network address translation (NAT): Yes | LED indicators: Power, LAN, WAN | Cables included: LAN (RJ-45) | USB 3.2 Gen 1 (3.1 Gen 1) Type-A ports quantity: 1 | Ethernet LAN data rates: 2500 Mbit/s | Width: 320 mm | AC input voltage: 110 - 240 V | AC input frequency: 50/60 Hz | Reset button: Yes | Security algorithms: WPA2-Personal | MAC address filtering: Yes | Security algorithms: SSH | Security algorithms: WPA-Enterprise | Wake-on-LAN ready: Yes | Security algorithms: WPA | Security algorithms: WPA3-Personal | Security algorithms: WPA3-Enterprise | Security algorithms: WPA-Personal | WLAN data transfer rate (max): 9400 Mbit/s | Security algorithms: WPA2-Enterprise | Power source type: AC | Security algorithms: WPS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950