

Mikrotik cAP ac 867 Mbit/s White Power over Ethernet (PoE)

Model: RBcAPGi-5acD2nD

Manufacturer: MIKROTIK

EAN: 4752224003416

Product Code: 378169

R2,173

Certification: CE, FCC, IC, EAC, ROHS | Receiver sensitivity: 2.4GHz: 1MBit/s: -100 @ 26dBm Tx 11MBit/s: -94 @ 26dBm Tx 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -78 @ 23dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -73 @ 22dBm Tx 5GHz: 6MBit/s: -96 @ 26dBm Tx 54MBit/s: -80 @ 21dBm Tx MCS0: -96 @ 26dBm Tx MCS7: -75 @ 20dBm Tx MCS9: -70 @ 18dBm Tx | Antenna type: Internal | 2.4 GHz: Yes | Frequency band: 2.412 - 2.484, 5.15 - 5.875 GHz | Warnings: Make sure the unit is stably mounted and ventilated. | Warnings: Do not open the appliance - risk of electric shock. | Warnings: Do not use in damp conditions. | Antennas quantity: 4 | Power consumption (max): 13 W | Processor frequency: 716 MHz | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.3at | Power over Ethernet (PoE): Yes | Networking standards: IEEE 802.11b | Networking standards: IEEE 802.3af | Harmonized System (HS) code: 85176990 | PoE adapter included: Yes | Internal memory: 128 MB | Width: 136 mm | Depth: 30 mm | Product colour: White | AC adapter included: Yes |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Antenna gain level (max): 2.5 dBi | Mounting kit: Yes | Processor model: IPQ4018 | Operating temperature (T-T): -40 - 50 °C | Maximum data transfer rate (5 GHz): 867 Mbit/s | Internal: No | Ethernet LAN (RJ-45) ports: 2 | 5 GHz: Yes | Flash memory: 16 MB | Antenna features: Integrated antenna | Maximum data transfer rate (2.4 GHz): 300 Mbit/s | DC voltage range: 17 - 57 V | Placement: Ceiling, Wall | Ethernet LAN data rates: 1000 | Operating system installed: RouterOS | Built-in processor: Yes | Ethernet LAN data rates: 10 | LED indicators: Yes | Ethernet LAN data rates: 100 | Power over Ethernet (PoE) type supported: Active PoE | Maximum data transfer rate: 867 Mbit/s | Output voltage: 57 V | Height: 136 mm | Power over Ethernet (PoE) type supported: Passive PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950