



Alienware AW3225DM computer monitor 80 cm (31.5) 2560 x 1440 pixels Wide Quad HD LCD Blue

Model: 210-BQWN

Manufacturer: DELL

EAN: 5397184962725

Product Code: 378393

R5,951

Certification: TÜV Rheinland | Bezel width (top): 8.2 mm | VESA mounting: Yes | Display technology: LCD | Power consumption (standby): 0.3 W | Power consumption (max): 90 W | Power consumption (typical): 33 W | Supported video modes: 2160p | Touchscreen: No | Supported video modes: 480p | Supported video modes: 1080p | Viewable size, horizontal: 69.7 cm | Supported video modes: 1080i | Cables included: USB Type-A to USB Type-B | HDMI version: 2.1 | Warnings: Avoid direct contact with liquids. | USB Type-A downstream ports quantity: 2 | Built-in speaker(s): No | Warnings: The monitor contains materials that may be harmful to the environment follow local regulations for the disposal of electronic devices. | Contrast ratio (typical): 3000:1 | Built-in camera: No | Headphone out: No |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Weight (without stand): 6.58 kg | Height adjustment: Yes | Backlight type: Edge LED | Cables included: DisplayPort | Plug and Play: Yes | AMD FreeSync: Yes | On Screen Display (OSD): Yes | Energy efficiency scale: A to G | HDMI cable length: 1.8 m | VESA Adaptive Sync support: Yes | High Dynamic Range (HDR) supported: Yes | DCI-P3 coverage: 95% | Width (without stand): 707.4 mm | Feet colour: Blue | Tilt adjustment: Yes | Windows operating systems supported: Windows 10 | Horizontal scan range: 30 - 285 kHz | Supported video modes: 576p | Viewable size, vertical: 39.2 cm | Maximum refresh rate: 180 Hz | Dell ComfortView technology: Yes | Stand included: Yes | Front bezel colour: Black | Bezel width (bottom): 1.82 cm | Built-in USB hub: Yes | Response time (extreme): 1 ms | HDMI ports quantity: 2 | High Dynamic Range (HDR) technology: DisplayHDR 400 | Supported video modes: 720p | Flicker-free technology: Yes | Response time (fast): 4 ms | Warnings: Do not expose to water or excessive moisture. | Windows operating systems supported: Yes | Cables included: HDMI | Pixel density: 93 ppi | Market positioning: Gaming | Panel type: VA | HDMI: Yes | Depth (without stand): 121.7 mm | Height (without stand): 418.7 mm | Weight (with stand): 9.19 kg | DisplayPort cable length: 1.8 m | Non-operating altitude: 0 - 12192 m | Viewable size diagonal: 80 cm | Compliance certificates: RoHS | Vertical scan range: 48 - 180 Hz | Low Blue Light technology: Yes | HDCP version: 1.4/2.3 | Picture-in-Picture: Yes | Picture-by-Picture (PbP): Yes | European Product Registry for Energy Labelling (EPREL) code: 2167431 | Surface hardness: 3H | Power supply type: Internal | Cable management: Yes | Anti-glare screen: Yes | Bezel width (side): 8.47 mm | Response time measurement type: GTG (Gray to Gray) | Adjustable height (max): 11 cm | Panel mounting interface: 100 x 100 mm | Heat dissipation (typical): 112.6 BTU/h | Screen curvature rating: 1500R | Energy efficiency class (SDR): G | Doesn't contain: Arsenic | Energy consumption (HDR) per 1000 hours: 39 kWh | Doesn't contain: Mercury | Energy efficiency class (HDR): G | Number of USB Type-B upstream ports quantity: 1 | Doesn't contain: PVC/BFR | Energy consumption (SDR) per 1000 hours: 33 kWh | Display resolution: 2560 x 1440 pixels | AC input frequency: 50/60 Hz | Tilt angle range: -5 - 21° | Display brightness (typical): 400 cd/m² | LED backlight: Yes | Width (with stand): 707.4 mm | AC input voltage: 100 - 240 V | Cable lock slot: Yes | Native aspect ratio: 16:9 | Display diagonal: 80 cm (31.5") | Power consumption (off): 0.3 W | Product colour: Blue | HDCP: Yes | Operating temperature (T-T): 0 - 40 °C | Screen shape: Curved | LED indicators: Yes | Depth (with stand): 232 mm | Display number of colours: 1.07 billion colours | Pixel pitch: 0.2724 x 0.2724 mm | Response time: 4 ms | DisplayPorts quantity: 1 | Input current: 1.5 A | Storage relative humidity (H-H): 5 - 90% | Operating altitude: 0 - 5000 m | Cable lock slot type: Kensington | Supported graphics resolutions: 1152 x 864 (XGA+) | Supported graphics resolutions: 1280 x 800 | Storage temperature (T-T): -20 - 60 °C | Supported graphics resolutions: 640 x 480 (VGA) | Supported graphics resolutions: 1680 x 1050 (WSXGA+) | Supported graphics resolutions: 1280 x 1024 (SXGA) | Supported graphics resolutions:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

720 x 576 | Supported graphics resolutions: 1024 x 768 (XGA) | Supported graphics resolutions: 720 x 480 | Supported graphics resolutions: 720 x 400 | Supported graphics resolutions: 1280 x 720 (HD 720) | HD type: Wide Quad HD | Supported graphics resolutions: 1280 x 960 | Supported graphics resolutions: 2560 x 1440 | Supported graphics resolutions: 1440 x 900 | Supported graphics resolutions: 3840 x 2160 | NVIDIA G-SYNC: No | Viewing angle, horizontal: 178° | Height (with stand): 583.3 mm | DisplayPort version: 1.4 | Operating relative humidity (H-H): 10 - 80% | Supported graphics resolutions: 1920 x 1080 (HD 1080) | Supported graphics resolutions: 800 x 600 (SVGA) | Package weight: 13.7 kg | Viewing angle, vertical: 178°

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950