



InLine PoE+ Gigabit Network Injector Hub 8 Port (8x PoE+), 1Gb/s, 19" 1U



Model: 32308H

Manufacturer: INLINE

EAN: 4043718276028

Product Code: 406126

R4,209

8-port PoE+ injector hub with up to 30 W power per port (total up to 240 W)

Supports IEEE 802.3af/at for PoE and PoE+ devices such as IP cameras & access points

Wireless design for noiseless operation in a 19" rack (1U)

Triple protection: overcurrent, overvoltage and overheating protection per port

High energy efficiency with over 91% efficiency in operation

The InLine® PoE+ Gigabit network injector hub is the ideal solution for upgrading existing networks to Power over Ethernet – without having to replace existing switches. The hub offers eight RJ45 ports for data and power supply in accordance with IEEE 802.3af (PoE) and IEEE 802.3at (PoE+), each with up to 30 watts of output power per port. This allows network devices such as IP cameras or WLAN access points to be operated flexibly and independently of a power socket.

With a combined total PoE output of up to 120 watts via the power supply unit or 240 watts via the

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

screw terminal connection block, the injector hub is particularly powerful. The integrated protection function against overcurrent, overvoltage and overheating offers additional safety in professional network operation. Thanks to its fanless design, the device operates silently and is ideal for installation in offices or technical rooms.

The standard-compliant support of 10/100/1000Base-T enables flexible integration into a wide range of network infrastructures. LED indicators provide information on the operating status and active PoE connections at all times.

Technical specifications:

Ports DATA IN: 8x RJ45 10/100/1000Base-T, Auto-MDI/MDI-X

Ports DATA + PWR OUT: 8x RJ45 10/100/1000Base-T, Auto-MDI/MDI-X

PoE type: Endspan

PoE output: 48–56 V DC, max. 30 W per port

Total power: 120 W (240 W via screw terminal connection block)

Standards: IEEE 802.3, 802.3u, 802.3ab, 802.3af, 802.3at

Voltage input: 100–240 V AC, 47–63 Hz

Output voltage/current: 56 V DC / 2.2 A

Power consumption in idle mode: 0.16 W

Energy efficiency: 91.4%

LED indicators: PWR, PoE (1–8)

Dimensions: 188 x 120 x 44 mm

Weight: approx. 1.521 kg

Operating temperature: 0–40 °C

Storage temperature: -20–70 °C

Humidity: 20–95 %, non-condensing

Scope of delivery:

1x InLine® PoE+ Gigabit network injector hub 8 port

1x power supply

2x operating instructions (German/English)

2x 19" mounting bracket

6x screws for mounting bracket

4x rubber feet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950