



InLine Network Switch 8-Port, 1Gb/s, Desktop, Metal, fanless, shielded ports



Model: 32308M

Manufacturer: INLINE

EAN: 4043718257331

Product Code: 406127

R1,531

Reliable gigabit data transmission:Eight RJ45 ports with 10/100/1000 Mb/s auto-negotiation enable a stable and fast LAN connection without manual configuration.

Maintenance-free operation:As an unmanaged switch, the device is completely plug-and-play. It reduces set-up effort and minimizes sources of error during operation.

Silent metal housing:The fanless design ensures silent operation. At the same time, the metal housing supports effective heat dissipation.

Flexible installation options:The compact desktop format and prepared wall mounting enable space-saving integration in different environments.

Stable network performance:Store-and-forward technology, flow control and a MAC address table with 8K entries support reliable data processing even with higher network loads.

The InLine® 8 Port Gigabit Switch is a reliable solution for expanding existing network structures. It

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

enables the simple connection of multiple Ethernet end devices via eight RJ45 ports with 10/100/1000 Mb/s auto-negotiation. Operation is unmanaged and completely plug-and-play. No configuration is required. The fanless metal housing supports noiseless continuous operation and ensures efficient heat dissipation. The integrated store-and-forward technology and flow control in full-duplex and asymmetric mode contribute to stable and low-loss data transmission. The compact desktop design and the pre-punched mounting points on the underside allow the switch to be positioned flexibly or mounted on the wall. The automatic detection of transmission speeds and Auto MDI/MDIX simplify integration into existing LAN structures. The switch is designed for reliable use in wired networks.

IEEE802.3i 10Base-T

IEEE802.3u 100Base-TX

IEEE802.3ab 1000Base-T

CSMA/CD

TCP/IP

IEEE802.3x Flow-Control full duplex

IEEE802.3z Flow-Control asymmetric

Backbone bandwidth 1 Gb/s

Forwarding rate 10Base-T 14880 pps/port

Forwarding rate 100Base-TX 148800 pps/port

MAC address table 8K

Auto MDI/MDIX

External power supply 5.0 V / 1.0 A