



InLine PoE+ Gigabit Network Switch 24 port, 1 Gb/s, 2xSFP, 19"1U (incl. brackets)



Model: 32316P

Manufacturer: INLINE

EAN: 4043718300686

Product Code: 406130

R7,920

The InLine® PoE++ Gigabit Network Switch is a fast and flexible solution for upgrading the existing network to the Power over Ethernet System IEEE 802.3af / 802.at / 802.3bt as well as a fiber-optic connection to bridge longer distances.

The switch provides protection against, for example, overload, overvoltage and overheating at each port. In addition, the switch offers IEEE 802.3af/at PoE+ on ports 5-16 with up to 32 watts of power and IEEE 802.3bt PoE++ on ports 1-4 with up to 60 watts of power via single Cat. 5e/6/6A/8.1 Ethernet cable with a PoE budget of 300W and a combined total power of 330W.

16x 10/100/1000MBit/s PoE ports solve the problem of a limited number of available power outlets, providing system administrators with a flexible solution to power almost anywhere the powering

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

network device, such as PoE-enabled IP cameras or wireless Access Points (with heating also).

The switch menu can be password protected to prevent unauthorized access.

- Standards:

IEEE 802.3 10Base-T, IEEE 802.3u 100Base-TX, IEEE 802.3ab 1000Base-T, IEEE 802.3z 1000Base-SX Gbit/s Ethernet over Fiber-Optic, IEEE 802.3x Full Duplex and flow control, IEEE 802.3af Power over Ethernet, IEEE 802.3at Power over Ethernet Plus, IEEE 802.3bt Power over Ethernet ++, IEEE 802.3az Energy Efficient Ethernet

- Ports: 16x 10/100/1000Base-T RJ45, Auto-MDI/MDI-X, 2x 1000Mb/s SFP

- PoE ports: 16 (PoE++ 1-4 / PoE+ 5-16)

- PoE budget 300W

- Total output: 330W

- LCD display: Real-time display of PoE operating status

- PoE output power: Port 1-4 max. 60W, port 5-16 max. 32W

- Network cable: Cat. 5e/6/6A/8.1 cable ($\leq$ 100m)

- 1000Base-X: MMF, SMF

- MAC address table: 8K, automatic learning, automatic updates

- Jumbo Frame: 9216 Bytes

- Packet buffer: 4.1Mbit

- Transmission method: Store-and-forward

- Packet forwarding rate: 26.78 million packages per second

- Bandwidth: 36Gbit

- Number of fans: 3

- Dimensions: (W x D x H): 440x232x45mm

- Weight: approx. 3.2kg

- Mains input: 100~240V AC, 50/60Hz

- Environmental conditions:

Operating temperature -10-60°C, storage temperature -40-70°C, humidity in operation 10-90% non condensing, humidity during storage 5-90% non condensing

- Surge protection: $\pm$ 6KV