

AG Neovo PM-3202 Signage Display Digital signage flat panel 81.3 cm (32) TFT 350 cd/m Full HD Black 16/7



Model: PM-3202

Manufacturer: AG NEOVO

EAN: 4710739597028

Product Code: 47370

R6,599

Noise reduction: Yes | USB ports quantity: 1 | Vertical scan range: 48 - 85 Hz | Cables included: HDMI | Microphone in: Yes | Surface hardness: 3H | USB port: Yes | USB version: 2.0 | Touchscreen: No | On Screen Display (OSD): Yes | Display brightness: 350 cd/m² | Operating hours (hours/days): 16/7 | Built-in speaker(s): Yes | Remote control included: Yes | RMS rated power: 20 W | HDMI input ports quantity: 3 | Contrast ratio (typical): 4000:1 | Wi-Fi: No | VESA mounting: Yes | Power adapter included: Yes | Product design: Digital signage flat panel | Pixel pitch: 0.364 x 0.364 mm | Haze rate: 2% | Panel mounting interface: 200 x 200 mm | Remote (IR) input: 1 | Power consumption (standby): 0.5 W | Display technology: TFT | Power consumption (typical): 42 W | Computer system: No | LED

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices

may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or

typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

backlighting type: LED | Horizontal scan range: 28 - 92 kHz | DVI port: No | Panel type: VA | Built-in processor: No | Panel mounting interface: 100 x 100 mm | Number of built-in speakers: 2 | HDMI version: 2.0 | RS-232 interface: Yes | HDMI ports quantity: 3 | Ethernet LAN: Yes | Purpose: Universal | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Unplug the monitor from the power source before cleaning. | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Energy efficiency class (SDR): G | Operating temperature (T-T): 0 - 40 °C | Operating relative humidity (H-H): -20 - 60% | Display resolution: 1920 x 1080 pixels | AC input frequency: 50 - 60 Hz | Ethernet LAN (RJ-45) ports: 1 | Ethernet LAN data rates: 100 | Ethernet LAN data rates: 10 | Display diagonal: 81.3 cm (32") | Product colour: Black | Storage temperature (T-T): 20 - 80 °C | HD type: Full HD | Viewing angle, vertical: 178° | Ethernet LAN data rates: 1000 Mbit/s | Quick start guide: Yes | Display number of colours: 16.7 million colours | Response time: 5 ms | Power consumption (off): 0.3 W | Viewing angle, horizontal: 178° | Storage relative humidity (H-H): 10 - 90% | AC input voltage: 100 - 240 V

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950