



Philips 1000 series 24E1N1100A/00 LED display 60.5 cm (23.8) 1920 x 1080 pixels Full HD LCD Black

Model: 24E1N1100A/00

Manufacturer: PHILIPS

EAN: 8712581804244

Product Code: 47391

R1,707

Compatible operating systems: Mac OS X Windows 11 / 10 | Colour gamut standard: sRGB | Non-operating altitude: 3658 - 12192 m | On Screen Display (OSD): Yes | Maximum refresh rate: 100 Hz | Touchscreen: No | Panel type: IPS | Backlight type: W-LED | Doesn't contain: Mercury | Doesn't contain: BFR | HDMI: Yes | Display diagonal (metric): 60.5 cm | Width (without stand): 542 mm | Panel mounting interface: 100 x 100 mm | VGA (D-Sub) ports quantity: 1 | Market positioning: Home | VESA Adaptive Sync support: Yes | Weight (without stand): 2.57 kg | Tilt adjustment: Yes | Audio output: Yes | Plug and Play: Yes | Stand included: Yes | Height (without stand): 316 mm | Depth (without stand): 45 mm | Built-in camera: No | Surface hardness: 3H | DDC/CI: Yes | Energy efficiency class (SDR): D | Anti-glare screen: Yes | On Screen Display (OSD) languages: Russian | On Screen

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Display (OSD) languages: Czech | Number of speakers: 2 | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: Ukrainian | On Screen Display (OSD) languages: Finnish | On Screen Display (OSD) languages: Japanese | On Screen Display (OSD) languages: Traditional Chinese | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Korean | Haze rate: 25% | Dynamic contrast ratio marketing name: Mega Infinity DCR | Heavy metals free: Hg (mercury) | On Screen Display (OSD) languages: Spanish | Viewable size, vertical: 29.6 cm | Sustainability compliance: Yes | Contrast ratio (typical): 1300:1 | Weight (with stand): 2.92 kg | Feet colour: Black | Display sRGB: Yes | Pixel density: 92.56 ppi | VESA mounting: Yes | LowBlue mode: Yes | Low Blue Light technology: Yes | Component video sync: Separate Sync | HDCP version: 1.4 | Doesn't contain: PVC | Power supply type: External | Number of OSD languages: 21 | Built-in USB hub: No | Viewable size, horizontal: 52.7 cm | Flicker-free technology: Yes | Built-in speaker(s): Yes | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Power consumption (standby): 0.5 W | AMD FreeSync: No | On Screen Display (OSD) languages: Swedish | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Simplified Chinese | On Screen Display (OSD) languages: Portuguese | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Greek | RMS rated power: 4 W | Energy efficiency class (HDR): Not available | Audio input: Yes | On Screen Display (OSD) languages: Turkish | EasyRead mode: Yes | Mean time between failures (MTBF): 50000 h | Response time (fast): 1 ms | Display technology: LCD | Picture enhancement: SmartImage game | Display brightness (typical): 300 cd/m² | Operating temperature (T-T): 0 - 40 °C | HD type: Full HD | Cable lock slot type: Kensington | Power consumption (off): 0.3 W | Viewing angle, horizontal: 178° | NVIDIA G-SYNC: No | Storage temperature (T-T): -20 - 60 °C | Display diagonal: 60.5 cm (23.8") | Vertical scan range: 48 - 60 Hz | Manual: Yes | Product colour: Black | Operating relative humidity (H-H): 20 - 80% | Width (with stand): 542 mm | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Package depth: 124 mm | Package width: 610 mm | Tilt angle range: -5 - 20° | Viewing angle, vertical: 178° | Horizontal scan range: 30 - 85 kHz | Depth (with stand): 180 mm | Screen shape: Flat | Height (with stand): 417 mm | Response time: 4 ms | Native aspect ratio: 16:9 | HDCP: Yes | Package weight: 4.68 kg | LED indicators: Stand-by | Display number of colours: 16.7 million colours | Operating altitude: 0 - 3658 m | AC input voltage: 100 - 240 V | LED indicators: Operation | Cable lock slot: Yes | Pixel pitch: 0.2745 x 0.2745 mm | Digital vertical frequency: 48 - 100 Hz | Compliance certificates: cTUVus | Compliance certificates: EAC | Compliance certificates: VCCI | Power consumption (typical): 14.5 W | Cables included: HDMI | HDMI ports quantity: 1 | Cables included: AC | Compliance certificates: BSMI |

European Product Registry for Energy Labelling (EPREL) code: 1868751 | Compliance certificates:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Federal Communications Commission (FCC) | Compliance certificates: ICES | HDMI version: 1.4 | Compliance certificates: RoHS | Digital horizontal frequency: 30 - 115 kHz | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Warnings: Unplug the monitor from the power source before cleaning. | Package height: 370 mm | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950