

AG Neovo QM-4303 Flat panel monitor Digital Signage 43 500 cd/m 4K Ultra HD Black



Model: QM-4303

Manufacturer: AG NEOVO

EAN: 4710739598605

Product Code: 47730

R10,768

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Surface hardness: 3H | Remote (IR) output: 1 | Display brightness: 500 cd/m² | USB playback: Yes | Placement supported: Indoor | PC Audio in: Yes | USB port: Yes | Energy efficiency scale: A to G | Anti-glare screen: Yes | Display weight: 8 kg | Power consumption (standby): 0.5 W | Energy efficiency class (SDR): G | Panel type: VA | Remote control included: Yes | Compliance certificates: Low Voltage Directive (LVD) | Display width: 971 mm | Compliance certificates: WEEE | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: REACH | Number of built-in speakers: 2 | Built-in speaker(s): Yes | Display depth: 70 mm | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | Haze rate: 25% | Energy consumption (SDR) per 1000 hours: 99 kWh | USB ports quantity: 1 | Computer system: No | Built-in processor: No | Display height: 559 mm | Mounting type: Wall | USB version: 2.0 | Purpose: Universal | VGA (D-Sub) input ports: 1 | Orientation: Horizontal/Vertical | Operating hours

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

(hours/days): 24/7 | Hazard pictogram(s): GHS09: Environmental hazard | Hazard pictogram(s): GHS07: Harmful | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Warnings: Do not open the appliance housing, risk of electric shock. | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | DVI port: No | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN (RJ-45) ports: 1 | HD type: 4K Ultra HD | Product colour: Black | Power consumption (off): 0.3 W | Storage temperature (T-T): 20 - 80 °C | Package depth: 144 mm | Viewing angle, horizontal: 178° | Display diagonal: 109.2 cm (43") | Package weight: 11.5 kg | Response time: 5 ms | Cable lock slot type: Kensington | Product design: Digital signage flat panel | AC input voltage: 100 - 240 V | Cables included: HDMI | Touchscreen: No | Cables included: AC | Viewing angle, vertical: 178° | Wi-Fi: No | VESA mounting: Yes | Package width: 1075 mm | Batteries included: Yes | HDMI ports quantity: 2 | Pixel pitch: 0.245 x 0.245 mm | Display number of colours: 1,07G | Panel mounting interface: 300 x 300 mm | Ethernet LAN: Yes | HDMI version: 2.0 | RS-232 interface: Yes | Native aspect ratio: 16:9 | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Operating relative humidity (H-H): -20 - 60% | Display resolution: 3840 x 2160 pixels | AC input frequency: 50 - 60 Hz | Horizontal scan range: 15 - 135 kHz | Power consumption (typical): 102 W | Package height: 652 mm

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950