

AG Neovo QM-5503 Flat panel monitor Digital Signage 55 500 cd/m 4K Ultra HD Black



Model: QM-5503

Manufacturer: AG NEOVO

EAN: 4710739598612

Product Code: 47731

R13,627

Certification: CE LVD WEEE RoHS REACH EAC UKCA | Touchscreen: No | Batteries included: Yes | RS-232 interface: Yes | Panel type: VA | Power consumption (standby): 0.5 W | Remote control included: Yes | Energy efficiency class (SDR): G | Wi-Fi: No | VESA mounting: Yes | Built-in processor: No | Contrast ratio (typical): 4000:1 | RMS rated power: 2 x 10 W | HDMI version: 2.0 | HDMI ports quantity: 2 | Energy consumption (SDR) per 1000 hours: 134 kWh | Mounting type: Wall | Ethernet LAN: Yes | USB version: 2.0 | Purpose: Universal | Compliance certificates: RoHS | Compliance certificates: CE | Compliance certificates: REACH | Compliance certificates: WEEE | Compliance certificates: Low Voltage Directive (LVD) | Panel mounting interface: 300 x 300 mm | Placement supported: Indoor | USB port: Yes | Built-in speaker(s): Yes | DVI port: No | Warnings: Do not open the appliance housing, risk of electric shock. | Warnings: The monitor contains substances hazardous to health, including mercury avoid contact with damaged parts. | Hazard pictogram(s): GHS09:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

Environmental hazard | Hazard pictogram(s): GHS07: Harmful | Warnings: The product should be disposed of by specialist disposal facilities for electronic equipment. | Remote (IR) output: 1 | Anti-glare screen: Yes | Display brightness: 500 cd/m² | Energy efficiency scale: A to G | Display weight: 13 kg | Display width: 1238.4 mm | PC Audio in: Yes | USB ports quantity: 1 | Display depth: 70 mm | Haze rate: 25% | Computer system: No | Orientation: Horizontal/Vertical | VGA (D-Sub) input ports: 1 | Display height: 709.2 mm | Number of built-in speakers: 2 | USB playback: Yes | Operating hours (hours/days): 24/7 | Surface hardness: 3H | Power consumption (typical): 102 W | Native aspect ratio: 16:9 | AC input voltage: 100 - 240 V | Package weight: 17.6 kg | Viewing angle, horizontal: 178° | Storage temperature (T-T): 20 - 80 °C | Operating temperature (T-T): 0 - 40 °C | Package height: 830 mm | Cables included: HDMI | HD type: 4K Ultra HD | Package width: 1390 mm | Product colour: Black | Pixel pitch: 0.245 x 0.245 mm | Cables included: AC | Display number of colours: 1,07G | Ethernet LAN (RJ-45) ports: 1 | Response time: 5 ms | Package depth: 144 mm | Cable lock slot type: Kensington | Display resolution: 3840 x 2160 pixels | Viewing angle, vertical: 178° | Product design: Digital signage flat panel | Power consumption (off): 0.3 W | Horizontal scan range: 15 - 135 kHz | Storage relative humidity (H-H): 10 - 90% | Vertical scan range: 24 - 85 Hz | Operating relative humidity (H-H): -20 - 60% | Display diagonal: 139.7 cm (55") | AC input frequency: 50 - 60 Hz

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950