# TP-Link Omada IES206G network switch Managed Gigabit Ethernet (10/100/1000) Black

Model: IES206G

Manufacturer: TP-LINK

EAN: 1210002602075

Product Code: 550129

## R4,118

- 6× Gigabit Ports (4× RJ45, 1× Combo RJ45/SFP, 1×SFP)
- Professional Industrial-Grade Design: -40~75°C Operating Temperature, 6kV Lighting Protection, and 1+1 Redundant Power Input
- Abundant Features: VLAN, QoS, and STP/RSTP
- Centralized Cloud Management via the Web or Omada App†
- Durable IP40 Aluminum Casing and DIN-rail / Wall-mount Design

Summary: TP-Link Omada IES206G. Switch type: Managed. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000). Basic switching RJ-45 Ethernet ports quantity: 4. MAC address

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

table: 8000 entries, Switching capacity: 12 Gbit/s. Networking standards: IEEE 802.1D, IEEE 802.1Q, IEEE 802.1p, IEEE 802.1w, IEEE 802.3ab, IEEE 802.3u, IEEE 802.3x. DC input voltage: 9 - 60 V. Wall mountable | Vendor Homepage: https://www.tp-link.com/nl/business-networking/omada-switch-industrial/ies206g/?app=t | Perjungimo tipas: Valdomas | Paslaugos kokybės (QoS) palaikymas: Taip | Duomenys perduodami į debesies platformą: Taip | Web pagrįstas valdymas: Taip | Pagrindinių perjungimo RJ-45 eterneto prievadų skaičius: 4 | Pagrindinių perjungimo RJ-45 eterneto prievadų tipas: Gigabit Ethernet (10/100/1000) | Jungtinių SFP prievadų skaičius: 1 | SFP modulio angų kiekis: 1 | Tinklo standartai: IEEE 802.1D/IEEE 802.1p/IEEE 802.1Q/IEEE 802.1w/IEEE 802.3ab/IEEE 802.3u/IEEE 802.3x | 10G parama: Ne | Portų mirroring: Taip | Aprėpties medžio protokolas: Taip | Auto MDI/MDI-X: Taip | Automatinis suderinimas (Auto-negotiation): Taip | Nuorodų agregacija: Taip | Srauto kontrolės palaikymas: Taip | Perjungimo pajėgumas: 12 | Persiuntimo dažnis: 8.93 | Adreso lentelės dydis: 8000 | „Store-and-forward“ funkcija: Taip | Jumbo Frames palaikymas: Taip | „Jumbo“ kadrai: 15000 | DHCP funkcijos: DHCP client | IGMP tinklinio judėjimo sekimas: Taip | Multicast palaikymas: Taip | Produkto spalva: Juoda | DIN bėgelių blokas: Taip | Montuojamas ant sienos: Taip | Be ventiliatoriaus: Taip | Maitinimo šaltinis: DC | Pridėtas maitinimo šaltinis: Taip | Nereikalingos maitinimo (RPS) paramos: Taip | DC įėjimo įtampa: 9 - 60 | Maitinimas per Eternetą (PoE): Ne | Darbo temperatūros diapazonas (TT): -40 - 75 | Sandėliavimo temperatūros norma (T-T): -40 - 85 | Darbo santykinės drėgmės diapazonas: 5 - 95 | Sandėliavimo santykinis drėgmės diapazonas: 5 - 95 | Plotis: 129 | Ilgis: 95 | Aukštis: 45 | Sertifikavimas: FCC, CE, RoHS | Bruto svoris: 0.739 | Neto svoris: 0.5 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 17 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 8 | Vieneto gylis: 16.5 | Vieneto aukštis: 8 | Name: NET SWITCH 6PORT 10/100/1000M/OMADA IES206G TP-LINK | Model: IES206G

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950