

**SSD MICRON  
7600 MAX 1600  
GB NVMe Yes  
NAND flash type  
TLC (Triple Level  
Cell)  
MTFDLCE1T6THS-  
1BP1DFCYR**



Model: MTFDLCE1T6THS-1BP1DFCYR

Manufacturer: MICRON

Product Code: 550398

**R10,060**

**Micron 7600 SSD: The PCIe® Gen5 SSD with leading quality of service for AI and mainstream data center workloads**

Imagine a world where your data center operations are performant, efficient, exceptionally responsive, and secure. The Micron 7600 SSD is designed to transform this vision into reality.

**Class-leading PCIe Gen5 performance and power efficiency**

The Micron 7600 SSD delivers fast access across a broad range of mainstream workloads with power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

efficiency that helps reduce power consumption, contributing to a more sustainable data center.

### **Exceptional workload responsiveness with best-in-class QoS and low latency**

Low and consistent latency delivers fast and predictable workload responsiveness. The Micron 7600 SSD demonstrates significantly lower and more consistent latency than other SSDs in its class.

### **Deploy with confidence: Micron innovation and leading Micron G9 NAND**

The Micron 7600 SSD is the world's first mainstream, data center SSD to use Micron G9 NAND. Its vertically integrated architecture, including Micron DRAM, NAND, controller, and firmware, helps simplify qualification across multiple SSDs.

### **Superior performance and power efficiency for mainstream workloads**

The Micron 7600 SSD enables class-leading performance for AI, databases, content delivery, real-time analytics, social media, cloud computing, and virtualization.

### **Low, consistent latency enables fast and predictable response times**

The Micron 7600 SSD is the leader in low, consistent latency. Latency-sensitive applications show up to 59% better latency consistency when reading data, and up to 76% better with mixed read and write.

### **Leading-edge Micron technology and security**

The Micron 7600 is the world's first mainstream data center SSD to use Micron G9 NAND, with an industry-leading NAND transfer speed of 3.6 GB/s.

The Micron 7600 SSD incorporates leading security features like hardware root of trust, securely signed firmware, and SPDM 1.2 (attestation) for identity authentication & firmware verification. It offers options for FIPS 140-3 Level 2 and TAA compliance. Selfencrypting drive (SED) option helps keep your data safe by adding AES-256 encryption for hardware-based data encryption, with no loss of SSD performance.

Summary: Micron 7600 PRO. SSD capacity: 1.6 TB, SSD form factor: E1.S, Component for:

Server/workstation | Vendor Homepage: <https://www.micron.com/search->

[results?searchRequest=MTFDLBQ12T8THS&activeTab=search-products](https://www.micron.com/search-results?searchRequest=MTFDLBQ12T8THS&activeTab=search-products) | SSD capacity: 1600 | SSD form factor: E1.S | Interface: PCI Express 5.0 | NVMe: Yes | NVMe version: 2.0 | Memory type: 3D TLC NAND | Component for: Server/workstation | Hardware encryption: Yes | Random read (4KB): 1800 |

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](https://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950

Random write (4KB): 260 | Read latency: 75 | Write latency: 15 | Uncorrectable Bit Error Rate (UBER):  
< 1 per 10<sup>17</sup> bits read | Average power consumption (read): 14 | Average power consumption  
(write): 14 | Quick start guide: Yes | Operating temperature (T-T): 0 - 70 | Compliance certificates:  
BSMI/China RoHS/RoHS | Warranty period: 5 | Unit Calculated Weight: 0.16 | Product Net Weight: 0.1  
| Unit Calculated Volume: 0.0002126 | Units per Shipping Box: 1 | Name: SSD PCIE G5 E1.S NVME  
1.6TB/7600 MAX MTFDLCE1T6THS MICRON | Model: MTFDLCE1T6THS-1BP1DFCYR | SSD series:  
7600 MAX

---

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](http://shop.cssi.co.za) | [sales@cssi.co.za](mailto:sales@cssi.co.za) | +27 (11)541-9950