



NET SWITCH 8PORT SFP56/CRS8128DS- 2DQ-2DDQ-RM MIKROTIK

Model: CRS812-8DS-2DQ-2DDQ-RM

Manufacturer: MIKROTIK

EAN: 4752224009715

Product Code: 550404

R23,441

This switch is your next leap forward – a powerful, efficient, and cost-effective way to bring 50G, 200G, and 400G into your rack. Quad-core 2 GHz ARM CPU, dual-redundant power supplies and 4x hot-swap cooling fans, 2x 10G Ethernet, 8x 50G SFP56, 2x 200G QSFP56, and 2x 400G QSFP56-DD ports.

The CRS812 DDQ is your next leap forward -

a powerful, efficient, and cost-effective way to bring 50G, 200G, and 400G into your rack

400G used to mean expensive, complex, and out of reach.

The CRS812 DDQ changes that!

With a modern Marvell switch chip and powerful ARM CPU, it delivers advanced routing, switching,

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

and traffic management features trusted in millions of RouterOS deployments – now with ports up to 400 Gbps!

- 4 GB of RAM
- Quad-core 2 GHz ARM CPU
- Dual-redundant hot-swappable power supplies
- 4x hot-swappable cooling fans
- RouterOS v7

Summary: Mikrotik CRS812 DDQ. Basic switching RJ-45 Ethernet ports type: 10G Ethernet (100/1000/10000), Basic switching RJ-45 Ethernet ports quantity: 2, Console port: RJ-45. DC input voltage: 12 V. Rack mounting | Vendor Homepage: <https://mikrotik.com/> | Pagrindinių perjungimo RJ-45 Ethernet prievadų skaičius: 2 | Pagrindinių perjungimo RJ-45 Ethernet prievadų tipas: 10G Ethernet (100/1000/10000) | 10 Gb Ethernet (varinių) lizdų skaičius: 2 | Fibre kanalo portai: 12 | Šviesolaidžio optinė jungtis: QSFP56/SFP56 | Konsolės prievadas: RJ-45 | QSFP56 prievadų kiekis: 8 | 10G parama: Taip | Stovo montavimas: Taip | Tarptautinės apsaugos (IP) kodas: IP20 | Ventiliatorių skaičius: 4 | Numatyta operacinė sistema: RouterOS | Integruotas procesorius: Taip | Procesoriaus gamintojas: ARM | Procesoriaus dažnis: 2000 | Atminties tipas: DDR4-SDRAM | Vidinė atmintis: 4000 | Flash atmintis: 512 | Vidutinis laikas tarp trikčių (MTBF): 200000 | Maitinimo šaltinis: AC | Pridėtas maitinimo šaltinis: Taip | Maitinimo šaltinių skaičius: 2 | AC įėjimo įtampa: 100 - 240 | AC įėjimo dažnis: 50/60 | DC įėjimo įtampa: 12 | Įvesties srovė: 20.8 | Galios suvartojimas (maks.): 134 | Darbo temperatūros diapazonas (TT): -10 - 50 | Plotis: 443 | Ilgis: 268 | Aukštis: 44 | Pridėti kabeliai: AC | Stovo montavimo rinkinys: Taip | Atitikties sertifikatai: CE/EAC/RoHS | Bruto svoris: 5.07 | Neto svoris: 2.8 | Vienetų skaičius vienoje siuntimo dėžėje: 2 | Vieneto plotis: 50 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 17.5 | Vieneto gylis: 38 | Vieneto aukštis: 7.5 | Name: NET SWITCH 8PORT SFP56/CRS8128DS-2DQ-2DDQ-RM MIKROTIK | Model: CRS812-8DS-2DQ-2DDQ-RM

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950