




Dahua Technology DHI- LM86-S400 Signage Display Digital signage flat panel 2.18 m (86") LCD 350 cd/m² 4K Ultra HD Black

Model: DHI-LM86-S400

Manufacturer: DAHUA

EAN: 6939554907234

Product Code: 550627

R37,241

- Hardware shell, profile frame design, beautiful and generous
- 178°H/178°V ultra-wide viewing Angle, overall viewing performance
- High fidelity digital processing, exciting and vivid video
- 8ms fast response time, no image blur or ghost
- Support HDMI, VGA and other signal input

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Built-in speaker
- Dual control mode of physical button and infrared remote control
- Low energy consumption and long service life

Summary: Dahua Technology DHI-LM86-S400. Product design: Digital signage flat panel. Display diagonal: 2.18 m (86"), Display technology: LCD, Display resolution: 3840 x 2160 pixels, Display brightness: 350 cd/m², HD type: 4K Ultra HD. Product colour: Black | Vendor Homepage: <https://www.dahuasecurity.com> | Display brightness: 350 | Display diagonal: 86 | Display resolution: 3840 x 2160 | Display technology: LCD | HD type: 4K Ultra HD | LED backlight: Yes | LED backlighting type: Direct-LED | Native aspect ratio: 16:9 | Native refresh rate: 60 | Panel type: ADS | Response time: 8 | Touchscreen: No | Viewing angle, horizontal: 178 | Viewing angle, vertical: 178 | DVI port: No | HDMI ports quantity: 2 | RS-232 interface: Yes | USB port: Yes | USB ports quantity: 1 | VGA (D-Sub) input ports: 1 | Built-in speaker(s): Yes | Number of built-in speakers: 2 | RMS rated power: 20 | Panel mounting interface: 800 x 400 | Placement supported: Indoor | Product colour: Black | Product design: Digital signage flat panel | Screen shape: Flat | VESA mounting: Yes | Purpose: Universal | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Energy consumption (SDR) per 1000 hours: 170 | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): G | Energy efficiency scale: A to G | Power consumption (off): 0.3 | Power consumption (standby): 0.5 | Cables included: AC/HDMI | Mounting kit: Yes | Remote control included: Yes | Operating relative humidity (H-H): 10 - 85 | Operating temperature (T-T): 0 - 40 | Certification: CE, FCC | Power supply type: Internal | Data Sheet (Link): <https://eprel.ec.europa.eu/api/product/2030219/fiches?language=EN> | Energy efficiency class: G | EPREL Registration Number: 2030219 | EPREL Version Number: 2 | Product Net Weight: 46.5 | Shipping Box Height: 126 | Unit Calculated Volume: 0.6086 | Unit Calculated Weight: 55.7 | Units per Pallet: 0 | Units per Shipping Box: 1 | Model: LM86-S400 | Model name: DHI-LM86-S400

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950