

**Switch UBIQUITI
USW-16-POE
Type L2
Desktop/pedestal
Rack
16x10Base-T
100Base-TX
1000Base-T
2xSFP PoE ports
16 PoE+ ports 8
18 Watts USW-
16-POE**



Model: USW-16-POE

Manufacturer: UBIQUITI

EAN: 817882028547

Product Code: 552307

R7,263

Second-Generation UniFi Switching

We've redesigned our UniFi Switches from the ground up.

Near Silent Cooling

Our new airflow design reduces the need for fan usage.

Redundant Power System

UniFi SmartPower RPS, USP-RPS, is our PSU failover system.

Power Supply Failure

In the event of a UniFi switch power supply failure, the USP-RPS automatically supplies redundant power to the failed device.

UniFi SmartPower

One UniFi SmartPower device can support up to 6 devices until the failed device is replaced.

Touchscreen Display

The 1.3" touchscreen display allows easy monitoring and quick troubleshooting.

Summary: Ubiquiti UniFi 16-Port PoE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 16. Full duplex. Switching capacity: 36 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. DC input voltage: 44 - 57 V. Power over Ethernet (PoE). Rack mounting, Form factor: 1U | Vendor Homepage: <https://switch.ui.com/gen2/> | Switch layer: L2/L3 | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP module slots quantity: 2 | Auto MDI/MDI-X: Yes | Auto-sensing: Yes | Flow control support: Yes | Full duplex: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Port mirroring: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Forwarding rate: 26.78 | Jumbo frames support: Yes | Static route: Yes | Switching capacity: 36 | Throughput: 18000 | Authentication type: IEEE 802.1x,RADIUS | Form factor: 1U | LED indicators: Activity/Link/PoE/Speed/System | Product colour: Silver | Rack mounting: Yes | AC input frequency: 50 - 60 | AC input voltage: 100 - 240 | DC input voltage: 44 - 57 | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 32 | Power over Ethernet plus (PoE+) ports quantity: 8 | Total

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Power over Ethernet (PoE) budget: 48 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 200 | Height: 43.7 | Weight: 2800 | Width: 442.4 | Certification: CE, FCC, IC | Harmonized System (HS) code: 85176990 | Product Net Weight: 2.8 | Shipping Box Height: 34 | Unit Calculated Volume: 0.02387 | Unit Calculated Weight: 4.15 | Units per Shipping Box: 2 | Model name: USW-16-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950