



WRL ACCESS POINT/U6-MESH- PRO UBIQUITI



Model: U6-MESH-PRO

Manufacturer: UBIQUITI

EAN: 810084695180

Product Code: 552308

R5,065

Indoor/outdoor WiFi 6 AP with 4 spatial streams, an integrated super antenna, and a gigabit passthrough port. Long Description: Ubiquiti U6 Mesh Pro. 2.4 GHz, 5 GHz, Maximum data transfer rate: 2400 Mbit/s. Security algorithms: WPA, WPA-Enterprise, WPA-PSK, WPA2, WPA3. Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 9 W | Vendor Homepage: <https://store.ui.com/us/en/collections/unifi-wifi-outdoor-long-range/products/u6-mesh-pro> | Bullet Points:

- WiFi 6
- 4 spatial streams
- 185 m² (2,000 ft²) coverage with the integrated omnidirectional super antenna
- 350+ connected devices
- Powered using PoE
- GbE uplink with (1) GbE passthrough port
- Versatile wall and pole mounting
- Weatherproof (outdoor exposed)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Maximum data transfer rate: 2400 | Maximum data transfer rate (2.4 GHz): 573.5 | Maximum data transfer rate (5 GHz): 2400 | Ethernet LAN data rates: 10/100/1000 | Frequency band: 2.4 - 5 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.1Q | MIMO: Yes | MIMO type: Multi User MIMO | Model: U6-MESH-PRO | Model name: U6 Mesh Pro | Security algorithms: WPA/WPA2/WPA3/WPA-Enterprise/WPA-PSK | Placement: Pole,Wall | Product colour: White | Housing material: Polycarbonate (PC) | Antenna type: Internal | Antenna direction type: Omni-directional | VLAN support: Yes | Antenna gain level (max): 8 | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -30 - 60 | International Protection (IP) code: IPX6 | Quantity per pack: 1 | Width: 181.2 | Depth: 60.2 | AC adapter included: Yes | PoE adapter included: Yes | Height: 343.2 | Ethernet LAN (RJ-45) ports: 2 | Mounting kit: Yes | Reset button: Yes | Power over Ethernet (PoE): Yes | LED indicators: Yes | DC voltage range: 42.5 - 57 | Unit Calculated Weight: 2.5 | Product Net Weight: 0.819 | Unit Calculated Volume: 0.01817 | Units per Shipping Box: 3 | Quick start guide: Yes | Units per Pallet: 0 | Quality of Service (QoS) support: Yes | Shipping Box Height: 42 | Power consumption (max): 9 | Weight: 819 | Sustainability compliance: Yes | Recommended usage: Indoor/outdoor

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950