CSSi SA - "Securing Tomorrow, Today"
Waterfall Office Park, 28 Augrabies Rd Vorna Valley, Midrand, 1685
Generated: 2026-10-30 11:31



Access Point UBIQUITI IEEE 802.11a/b/g IEEE 802.11n IEEE 802.11ac IEEE 802.11ax 1x2.5GbE U7-PRO

Model: U7-PRO

Manufacturer: UBIQUITI

EAN: 810084693650

Product Code: 552311

R4,970

Ceiling-mounted WiFi 7 AP with 6 spatial streams and 6 GHz support for interference-free WiFi in demanding, large-scale environments.

- WiFi 7 tri-radio with 6 GHz
- 6 spatial streams
- 140 m² (1,500 ft²) coverage
- 300+ connected devices

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

- Powered using PoE+
- 2.5 GbE uplink

Summary: Ubiquiti U7 Pro. 2.4 GHz, 5 GHz, 6 GHz, Maximum data transfer rate: 5800 Mbit/s. Security algorithms: PPSK, WPA, WPA-Enterprise, WPA-PSK, WPA2, WPA3. Ethernet LAN data rates: 1000,2500 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 21 W | Vendor Homepage: https://eu.store.ui.com/eu/en/pro/category/whats-new/products/u7-pro | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: Yes | Maximum data transfer rate: 5800 | Maximum data transfer rate (2.4 GHz): 688 | Maximum data transfer rate (5 GHz): 4300 | Maximum data transfer rate (6 GHz): 5800 | Ethernet LAN data rates: 1000/2500 | Throughput data rate: 5765 | Frequency band: 2.4 - 6 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11b/IEEE 802.11be/IEEE 802.11g/IEEE 802.11k/IEEE 802.11n/IEEE 802.11r/IEEE 802.11v/IEEE 802.1Q/IEEE 802.3at | Coverage area: 140 | Number of users: 300 | MIMO: Yes | MIMO type: Multi User MIMO | Fit AP mode features: Hotspot 2.0 | Fast roaming: Yes | VLAN support: Yes | Rate limiting: Yes | Band steering: Yes | Quality of Service (QoS) support: Yes | Maximum Tx power (2.4 GHz): 22 | Maximum Tx power (5 GHz): 26 | Maximum Tx power (6 GHz): 23 | Security algorithms: PPSK/WPA/WPA2/WPA3/WPA-Enterprise/WPA-PSK | Ethernet LAN (RJ-45) ports: 1 | WAN connection: Ethernet (RJ-45) | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: PoE+ | DC voltage range: 44 - 57 | Power consumption (max): 21 | Placement: Ceiling,Wall | Product colour: White | Housing material: Metal,Polycarbonate (PC) | Reset button: Yes | LED indicators: Yes | Antenna type: Internal | Antenna gain level (max): 6 | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Width: 206 | Depth: 206 | Height: 46 | Weight: 680 | Quantity per pack: 1 | Mounting kit: Yes | Operating relative humidity (H-H): 5 - 95 | Operating temperature (T-T): -30 - 60 | Sustainability compliance: Yes | Unit Calculated Weight: 1.58 | Product Net Weight: 0.68 | Unit Calculated Volume: 0.01157 | Units per Shipping Box: 5 | Unit Width: 9.6 | Shipping Box Height: 32 | Unit Depth: 24.6 | Unit Height: 24.5 | Name: WRL ACCESS POINT/U7-PRO UBIQUITI | Model name: U7 Pro

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950