



Dahua Technology CHS4212-8GT- 110 network switch Managed L2 Gigabit Ethernet (10/100/1000) Power over Ethernet (PoE) Desktop Blue

Model: CHS4212-8GT-110

Manufacturer: DAHUA

EAN: 6939554981906

Product Code: 552339

R2,901

- Features managed mode

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

- Complies with IEEE802.3, IEEE802.3u, IEEE802.3x, IEEE802.3ab, IEEE802.3z, IEEE802.3az and IEEE802.3ad standards
- Meets the requirements of IEEE802.3af, IEEE802.3at, Hi-PoE and IEEE802.3bt standards
- Supports network topology visualization
- Supports mobile management by app
- Supports one-stop maintenance
- With its full metal design and dust-proof enclosure, it can be used in a wide range of temperatures
- Supports desktop mount and DIN rail mount

Summary: Dahua Technology CHS4212-8GT-110. Switch type: Managed, Switch layer: L2. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 10. MAC address table: 8000 entries, Switching capacity: 24 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at, IEEE 802.3bt. DC input voltage: 48 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE). Form factor: Desktop | Vendor Homepage:

<https://transmission.dahuasecurity.com/en/product->

[list/Business/CloudManagementSolution/NetworkSwitch/CHS4212-8GT-110](https://transmission.dahuasecurity.com/en/product-list/Business/CloudManagementSolution/NetworkSwitch/CHS4212-8GT-110) | Switch type: Managed | Switch layer: L2 | Cloud-managed: Yes | Web-based management: Yes | System event log: Yes | Basic switching RJ-45 Ethernet ports quantity: 10 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 10 | SFP module slots quantity: 2 | Power connector: DC-in jack | Networking standards: IEEE 802.3af/IEEE 802.3at/IEEE 802.3bt | 10G support: No | Switching capacity: 24 | Forwarding rate: 17.856 | MAC address table: 8000 | Jumbo frames support: Yes | Jumbo frames: 12288 | Packet buffer memory: 8.4 | Rack mounting: No | Form factor: Desktop | Product colour: Blue | Housing material: Iron | Reset button: Yes | LED indicators: Yes | DIN rail mounting: Yes | Mean time between failures (MTBF): 810020 | Power source: DC | Power supply included: Yes | DC input voltage: 48 - 57 | Input current: 2.5 - 2.1 | Power consumption (max): 117.2 | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) ports quantity: 8 | Total Power over Ethernet (PoE) budget: 110 | Operating temperature (T-T): -30 - 65 | Storage temperature (T-T): -40 - 85 | Operating relative humidity (H-H): 10 - 90 | Storage relative humidity (H-H): 5 - 95 | Width: 139.4 | Depth: 171.8 | Height: 42 | Weight: 660 | Cables included: AC | Package width: 253.5 | Package depth: 314.5 | Package height: 130.5 | Package weight: 1600 | Compliance certificates: CE | Unit Calculated Weight: 2 | Product Net Weight: 0.66 | Unit Calculated Volume: 0.01194 | Units per Shipping Box: 5 | Unit Width: 25 | Units per Pallet: 0 | Shipping Box Height: 27 | Unit Depth: 31.5 | Unit Height: 13 | Name: NET SWITCH 12PORT 8POE 1G/CHS4212-8GT-110 DAHUA | Model name:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950

