

Switch UBIQUITI Pro Max 48 Type L3 USW-PRO- MAX-48



Model: USW-PRO-MAX-48

Manufacturer: UBIQUITI

EAN: 810084692745

Product Code: 552348

R15,223

A 48-port, Layer 3 Etherlighting™ switch with 2.5 GbE.

- (16) 2.5 GbE RJ45 ports
- (32) GbE RJ45 ports
- (4) 10G SFP+ ports
- DC power backup ready
- Managed with UniFi Network 8.0.24 and later

Summary: Ubiquiti Pro Max 48. Switch layer: L3. Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500), Basic switching RJ-45 Ethernet ports quantity: 48. Switching capacity: 224 Gbit/s. Networking standards: IEEE 802.1x. Power connector: AC/DC. Rack mounting, Form factor: 1U | Vendor Homepage: <https://eu.store.ui.com/eu/en/pro/products/usw-pro-max-48> | Switch layer: L3 | 2.5G Ethernet (copper) ports quantity: 16 | Basic switching RJ-45 Ethernet ports quantity: 48 | Basic switching RJ-45 Ethernet ports type: 2.5G Ethernet (100/1000/2500) | Gigabit Ethernet (copper) ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 32 | Power connector: AC/DC | SFP+ module slots quantity: 4 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | Networking standards: IEEE 802.1x | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Voice VLAN | VLAN support: Yes | Forwarding rate: 166.656 | Jumbo frames support: Yes | Static route: Yes | Switching capacity: 224 | Throughput: 112 | DHCP features: DHCP relay/DHCP snooping | IGMP snooping: Yes | Loop protection: Yes | Display type: LCM | Form factor: 1U | Housing material: SGCC | LED indicators: Link/Network/Speed/Status | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | Stackable: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | Power consumption (max): 100 | Power source: AC/DC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 325 | Height: 43.7 | Weight: 4800 | Width: 442.4 | Cables included: Power | Mounting brackets included: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Product Net Weight: 4.9 | Shipping Box Height: 46 | Unit Calculated Volume: 0.03169 | Unit Calculated Weight: 6.58 | Units per Shipping Box: 2 | Model: USW-PRO-MAX-48 | Model name: Pro Max 48

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950