

Keenetic Explorer 4G (KN- 4910) AC1200 Mesh Wi-Fi 5 4G Modem Router with a 4-Port Smart Switch



Model: KN-4910-01-EU

Manufacturer: KEENETIC

EAN: 4897082922155

Product Code: 575675

R2,434

Supported protocols: EoIP, IP-IP, GRE | VPN support: PPTP (client/server), L2TP over IPSec client/server, OpenVPN client/server, SSTP client/server, IPsec VPN (client/server) | Supported WAN type: Multi-WAN | 4G bands supported: 900 | UDP-to-HTTP proxy: Yes | 4G bands supported: 2600 | 4G bands supported: 850 | 4G bands supported: 1800 | 4G bands supported: 2100 | 4G bands supported: 800 | WireGuard throughput: 45 Mbit/s | IntelliQoS: Yes | AdGuard ad blocker: Yes | Number of users: 199 user(s) | WLAN data transfer rate (second band): 867 Mbit/s | Wi-Fi Multimedia (WMM)/(WME): Yes | WireGuard: Yes | Cloudflare DNS: Yes | Intelligent Mesh technology: Yes | Parental control: Yes | Web-based setup wizard: Yes | 3G bands supported: 850 | Port triggering: Yes | 3G bands supported: 2100 | PPPoE/PPTP/L2TP pass-through: Yes | Mobile network generation: 4G |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Ping check: Yes | SIM card slot: Yes | L2TP/PPTP data rate: 95 Mbit/s | WPS push button: Yes | 3G/4G USB modem compatibility: No | Firewall security: SPI | Guest access: Yes | System event log: Yes | 3G standards: HSDPA | 3G standards: HSUPA | DSL WAN: No | IPv4 & IPv6 features: IPv6 SSH | SSID-based VLAN assignment: Yes | Policy-based routing: Yes | 4G bands supported: 2300 MHz | Command-line interface (CLI): Yes | IPv4 & IPv6 features: Dual stack IPv4/IPv6 | IGMP snooping: Yes | Port forwarding: Yes | SIM card type: NanoSIM | HTTPS security for access via KeenDNS: Yes | Captive portal: Yes | IPv4 & IPv6 features: IPv6 Telnet | 3G standards: WCDMA | 3G bands supported: 900 MHz | WLAN data transfer rate (first band): 300 Mbit/s | USSD request support: Yes | Switching protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | 4G bands supported: 2500 | 4G standard: LTE-TDD & LTE-FDD | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | WAN connection type: RJ-45, WISP | Short Message Service (SMS): Yes | 4G bands supported: 1900 | Traffic statistics: Yes | Routing table: DHCP | DoS attack prevention: Yes | Routing table: Manual | Direct or cloud access via KeenDNS: Yes | Universal Plug and Play (UPnP): Yes | Firewall: Yes | Cloud-managed: Yes | IPoE/PPPoE data rate: 95 Mbit/s | Internet connection backup: Yes | Dynamic DNS (DDNS): Yes | DHCP server: Yes | Schedule access: Yes | Number of guest networks (2.4 GHz): 7 | MU-MIMO technology: Yes | Antenna design: External | Number of guest networks (5 GHz): 7 | Bandwidth control: Yes | 4G data rate (max): 150 Mbit/s | Product colour: Grey | MIMO: Yes | Networking standards: IEEE 802.11a | Network address translation (NAT): Yes | Security algorithms: OWE | Networking standards: IEEE 802.11k | Ethernet LAN (RJ-45) ports: 4 | AC input frequency: 50/60 Hz | Security algorithms: WPA-PSK | Networking standards: IEEE 802.11v | Networking standards: IEEE 802.11r | Security algorithms: WPA2-PSK | Security algorithms: WPA2-Enterprise | Antenna connector type: SMA | Networking standards: IEEE 802.11b | Security algorithms: WPA3-PSK | Ethernet WAN: Yes | DHCP client: Yes | Stateful Packet Inspection (SPI): Yes | Cables included: LAN (RJ-45) | Processor frequency: 575 MHz | Weight: 236 g | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Ethernet LAN data rates: 100 Mbit/s | Product colour: White | Flash memory: 32 MB | Mobile operating systems supported: iOS | 3G: Yes | Networking standards: IEEE 802.1Q | Operating temperature (T-T): 0 - 40 °C | Processor model: MediaTek MT7628N | Security algorithms: WPA3-Enterprise | Power source type: AC | Networking standards: IEEE 802.11ac | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Ethernet LAN interface type: Fast Ethernet | Antenna type: External | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | Quick start guide: Yes | Web-based management: Yes | MAC address filtering: Yes | Security algorithms: WEP | AC adapter included: Yes | Backup function: Yes | AC input voltage: 100 - 240 V | Width: 159 mm | Output current: 1 A | Quick installation guide: Yes | Mobile operating systems supported: Android | Output voltage: 12 V |

Processor manufacturer: MediaTek | LED indicators: LAN, Power, WLAN | Antenna gain level (max): 4

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

dBi | Operating relative humidity (H-H): 20 - 95% | Internal memory type: DDR2 | Quality of Service (QoS) support: Yes | Built-in processor: Yes | Ethernet LAN: Yes | Depth: 110 mm | Supported network protocols: IPoE, PPPoE, PPTP, L2TP, 802.1x | USB port: No | Product type: Tabletop router | WLAN data transfer rate (max): 1200 Mbit/s | Number of products included: 1 pc(s) | Modem chipset: ASR1803S | Wi-Fi standards: Wi-Fi 4 (802.11n) | Height: 29 mm | Antennas quantity: 4 | Internal memory: 128 MB | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Cabling technology: 10/100Base-T(X)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950