

TP-Link Archer C64 wireless router Gigabit Ethernet Dual-band (2.4 GHz / 5 GHz) Black

Model: Archer C64

Manufacturer: TP-LINK

EAN: 1210002606936

Product Code: 575693

R1,301

Receiver sensitivity: 5 GHz: 11a 6Mbps:-95dBm 11a 54Mbps:-77dBm 11ac VHT20 MCS8:-71dBm 11ac VHT40 MCS9:-67dBm 11ac VHT80 MCS9:-63dBm 2.4 GHz: 11g 6Mbps: -96dBm 11g 54Mbps: -78dBm 11n HT20 MCS7:-77dBm 11n HT40 MCS7:-74dBm 11ac VHT20 MCS8:-73dBm 11ac VHT40 MCS9:-68dBm | Certification: CE, RoHS | Firewall: Yes | USB port: No | MU-MIMO technology: Yes | Antenna design: External | SIM card slot: No | Height: 27.9 mm | 3G/4G USB modem compatibility: No | Harmonized System (HS) code: 85176990 | Output current: 1 A | Product type: Tabletop router | WLAN data transfer rate (first band): 400 Mbit/s | URL filtering: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | WPS push button: Yes | WLAN data transfer rate (second band): 867 Mbit/s | Universal Plug and Play (UPnP): Yes | Guest access: Yes | Linux operating systems supported: Yes | Parental control: Yes | Supported network protocols: IPv4, IPv6 | Built-in processor: Yes | Dynamic DNS (DDNS): Yes | Transmit power: CE: 20dBm(2.4 GHz), 23dBm(5.15 GHz~5.25 GHz) FCC: 30dBm(2.4 GHz & 5 GHz) |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Firewall security: SPI | DMZ support: Yes | Port triggering: Yes | Port forwarding: Yes | DHCP server: Yes | Mac compatibility: Yes | Firmware upgradeable: Yes | Windows operating systems supported: Windows 10 | Web-based management: Yes | Security algorithms: WPA-Enterprise | Windows operating systems supported: Windows 7 | Cables included: LAN (RJ-45) | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Mac operating systems supported: Yes | Security algorithms: WPA | Windows operating systems supported: Windows 98SE | Networking standards: IEEE 802.1x | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 1200 Mbit/s | AC adapter included: Yes | Ethernet LAN: Yes | Wi-Fi standards: 802.11g | Depth: 120 mm | Quality of Service (QoS) support: Yes | Product colour: Black | Quick installation guide: Yes | Wi-Fi standards: 802.11a | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Antennas quantity: 4 | Wi-Fi standards: Wi-Fi 4 (802.11n) | Operating relative humidity (H-H): 10 - 90% | Reset button: Yes | Ethernet LAN (RJ-45) ports: 4 | Filtering: Yes | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows 8 | Ethernet WAN: Yes | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Output voltage: 12 V | Windows operating systems supported: Windows 2000 | Windows operating systems supported: Windows XP | Processor frequency: 1200 MHz | Width: 120 mm | Ethernet LAN interface type: Gigabit Ethernet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950