

TP-LINK ARCHER C64 dual-band W-Fi router, black



Model: Archer C64

Manufacturer: TP-LINK

EAN: 1210002606936

Product Code: 575693

R792

Receiver sensitivity: 5 GHz: 11a 6Mbps:-95dBm 11a 54Mbps:-77dBm 11ac VHT20 MCS8:-71dBm 11ac VHT40 MCS9:-67dBm 11ac VHT80 MCS9:-63dBm 2.4 GHz: 11g 6Mbps: -96dBm 11g 54Mbps: -78dBm 11n HT20 MCS7:-77dBm 11n HT40 MCS7:-74dBm 11ac VHT20 MCS8:-73dBm 11ac VHT40 MCS9:-68dBm | Certification: CE, RoHS | Reset button: Yes | Quality of Service (QoS) support: Yes | Filtering: Yes | AC adapter included: Yes | Product colour: Black | Mac operating systems supported: Yes | Firmware upgradeable: Yes | Networking standards: IEEE 802.1x | Security algorithms: WPA3 | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA-Enterprise | WLAN data transfer rate (max): 1200 Mbit/s | Web-based management: Yes | Security algorithms: WPA | Mac compatibility: Yes | Security algorithms: WPA2 | Security algorithms: WPA2-Enterprise | Processor frequency: 1200 MHz | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Operating relative humidity (H-H): 10 - 90% | Windows operating systems supported: Windows 98SE | Windows operating systems supported: Windows NT | Windows operating systems supported: Windows 7 | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 8.1 | Windows operating systems supported: Windows Vista | Windows operating systems supported: Windows 8 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Windows operating systems supported: Windows 2000 | Cables included: LAN (RJ-45) | Ethernet WAN: Yes | Windows operating systems supported: Windows 10 | Operating temperature (T-T): 0 - 40 °C | DHCP client: Yes | Quick installation guide: Yes | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | Ethernet LAN (RJ-45) ports: 4 | Ethernet LAN interface type: Gigabit Ethernet | Antennas quantity: 4 | Ethernet LAN: Yes | Depth: 120 mm | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Wi-Fi standards: 802.11a | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Firewall: Yes | Harmonized System (HS) code: 85176990 | Width: 120 mm | Output voltage: 12 V | Guest access: Yes | DHCP server: Yes | Firewall security: SPI | USB port: No | Output current: 1 A | SIM card slot: No | Product type: Tabletop router | Universal Plug and Play (UPnP): Yes | Supported network protocols: IPv4, IPv6 | Parental control: Yes | WLAN data transfer rate (second band): 867 Mbit/s | Height: 27.9 mm | 3G/4G USB modem compatibility: No | WLAN data transfer rate (first band): 400 Mbit/s | URL filtering: Yes | Built-in processor: Yes | Dynamic DNS (DDNS): Yes | Transmit power: CE: 20dBm(2.4 GHz), 23dBm(5.15 GHz~5.25 GHz) FCC: 30dBm(2.4 GHz & 5 GHz) | DMZ support: Yes | Port triggering: Yes | Port forwarding: Yes | Antenna design: External | Linux operating systems supported: Yes | MU-MIMO technology: Yes | WPS push button: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950