



Avtek TS 9 Mate G 65 interactive monitor



Model: 1TV436

Manufacturer: AVTEK

EAN: 5907731311434

Product Code: 575801

R30,629

Warnings: Do not use in a damp environment or near water. | Warnings: Avoid dropping or bumping the monitor. | EDLA certificate: YES | Warnings: Protect against the possibility of scratching the touchscreen. | Touch response time: 10 ms | Bluetooth: Bluetooth 5.4, Class 1 | Screen shape: Flat | Display diagonal: 165.1 cm (65") | Display resolution: 3840 x 2160 pixels | Operating temperature (T-T): 0 - 40 °C | Viewing angle, horizontal: 178° | HD type: 4K Ultra HD | Native aspect ratio: 16:9 | Product colour: Black | LED backlight: Yes | DisplayPorts quantity: 1 | Contrast ratio (typical): 5000:1 | USB Touch port: Yes | Native refresh rate: 60 Hz | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Serbian | Ethernet LAN: Yes | Cables included: Power | Windows operating systems supported: Windows XP | Windows operating systems supported: Windows 10 | Windows operating systems supported: Windows, Linux, Mac | Built-in speaker(s): Yes | Felt pens included: Yes | Panel type: VA | On Screen Display (OSD) languages: English | Cables included: HDMI | Windows operating systems supported: Windows 8 | Cables included: USB | Number of OSD languages: 12 | USB ports quantity: 7 | Product design: Interactive flat panel | Operating hours (hours/days): 24/7 | Display brightness: 500 cd/m² | Wall mountable: Yes | Audio ports quantity: 2 | Storage temperature (T-T): -20 - 60 °C | On Screen Display

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

(OSD): Yes | Display number of colours: 1.07 billion colours | Panel mounting interface: 600 x 400 | Package depth: 179 mm | Package height: 1012 mm | Windows operating systems supported: Windows 11 | Mac operating systems supported: Yes | Touchscreen: Yes | Number of simultaneous touchpoints (Windows): 50 | Viewing angle, vertical: 178° | Energy efficiency class (SDR): G | Built-in processor: Yes | Internal storage capacity: 64 GB | Remote control type: Y | European Product Registry for Energy Labelling (EPREL) code: 2663941 | RMS rated power: 2 x 25 W | Operating relative humidity (H-H): 10 - 90% | On Screen Display (OSD) languages: Ukrainian | Wi-Fi: Yes | Package width: 1620 mm | Operating time: 24 h | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Croatian | USB port: Yes | Panel life: 50000 h | DisplayPorts in: 1 | Operating system installed: Android 16 | Operating system installed: Android 16 | On Screen Display (OSD) languages: Bulgarian | Windows operating systems supported: Windows 7 | DFU / User manual: Yes | LED backlighting type: Direct-LED | HDMI ports quantity: 4 | On Screen Display (OSD) languages: LAT | OPS module slot: Yes | Number of built-in speakers: 2 | Touchscreen technology: Infrared | On Screen Display (OSD) languages: Polish | Mounting bracket(s) included: Yes | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Hungarian | On Screen Display (OSD) languages: Slovak | On Screen Display (OSD) languages: Lithuanian | Display technology: LED | On Screen Display (OSD) languages: Czech | Storage relative humidity (H-H): 10 - 90% | Linux operating systems supported: Yes | RS-232 interface: Yes | VESA mounting: Yes | OPS slot: 1 | Internal memory: 8 GB | Orientation: Horizontal

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950