

Mercusys 4G+ Cat6 AC1200 Wireless Dual Band Gigabit Router



Model: MB230-4G

Manufacturer: MERCUSYS

EAN: 6957939001827

Product Code: 576822

R2,118

Receiver sensitivity: 11g 6Mbps: -95dBm 11g 54Mbps: -77dBm 11n HT20 MCS7: -74dBm 11n HT40 MCS7: -71dBm 11a 6Mbps: -92dBm 11a 54Mbps: -75dBm 11ac VHT20 MCS8: -70dBm 11ac VHT40 MCS9: -65dBm 11ac VHT80 MCS9: -61dBm | Ethernet LAN data rates: 100 | Ethernet LAN interface type: Gigabit Ethernet | Output voltage: 12 V | Port forwarding: Yes | Package type: Box | WAN connection type: RJ-45 | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | 3G standards: HSPA+ | Wi-Fi standards: 802.11g | Security algorithms: WPA3-SAE | Ethernet LAN data rates: 1000 Mbit/s | DSL WAN: No | 3G standards: UMTS | Width: 95 mm | DHCP server: Yes | Product type: Desktop/pole router | UMTS bands supported: 850 | Height: 166 mm | Power source type: DC | UMTS bands supported: 2100 MHz | UMTS bands supported: 900 | Operating temperature (T-T): 0 - 40 °C | Firmware upgradeable: Yes | Ethernet LAN data rates: 10 | Number of products included: 1 pc(s) | 4G standard: LTE-TDD & LTE-FDD | Top Wi-Fi standard: Wi-Fi 5 (802.11ac) | Wi-Fi standards: Wi-Fi 5 (802.11ac) | Wi-Fi standards: 802.11b | Wi-Fi standards: 802.11a | Cabling technology:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

10/100/1000Base-T(X) | Ethernet WAN: Yes | Wi-Fi standards: Wi-Fi 4 (802.11n) | Product colour: White | AC adapter included: Yes | Storage temperature (T-T): -40 - 60 °C | 3G standards: HSPA | System event log: Yes | Ethernet LAN (RJ-45) ports: 2 | Security algorithms: WPA-PSK | Storage relative humidity (H-H): 5 - 90% | Security algorithms: WPA2-PSK | Networking standards: IEEE 802.11ac | Networking standards: IEEE 802.11a | Networking standards: IEEE 802.11g | Networking standards: IEEE 802.11n | WLAN data transfer rate (max): 1200 Mbit/s | Security algorithms: 64-bit WEP | Networking standards: IEEE 802.11b | Wi-Fi Multimedia (WMM)/(WME): Yes | Operating relative humidity (H-H): 10 - 90% | DC-in jack: Yes | Quick installation guide: Yes | Dual SIM support: No | Output current: 1 A | Universal Plug and Play (UPnP): Yes | USB port: No | Depth: 61 mm | SIM card slot: Yes | Ethernet LAN: Yes | SIM card type: NanoSIM | Port triggering: Yes | Indication light: Yes | Dynamic DNS (DDNS): Yes | DMZ support: Yes | Mobile network generation: 4G | Antenna design: Internal | 3G/4G USB modem compatibility: Yes | Port-based Network Access Control (PNAC): Yes | VoIP protocols: IPv4, IPv6 | 4G bands supported: 700 | 4G bands supported: 2300 | 4G bands supported: 900 | 4G bands supported: 1800 | 4G bands supported: 2600 | 4G bands supported: 850 | WPS push button: Yes | Firewall: Yes | 4G bands supported: 2100 | 4G bands supported: 800

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950