

TP-Link Omada 5-Port Gigabit Easy Managed Switch with 4- Port PoE+



Model: ES205GP

Manufacturer: TP-LINK

EAN: 8885020620931

Product Code: 576824

R1,670

Total Power over Ethernet (PoE) budget: 65 W | Operating temperature (T-T): 0 - 40 °C | Networking standards: IEEE 802.1Q | Storage relative humidity (H-H): 5 - 90% | Networking standards: IEEE 802.1ab | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Networking standards: IEEE 802.3x | Package type: Box | Networking standards: IEEE 802.1p | Networking standards: IEEE 802.3at | Basic switching RJ-45 Ethernet ports quantity: 5 | DHCP features: DHCP client | Reset button: Yes | VLAN support: Yes | IGMP snooping: Yes | Power supply included: Yes | Power over Ethernet (PoE) ports quantity: 4 | Operating relative humidity (H-H): 10 - 90% | 10G support: No | Width: 100 mm | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Power over Ethernet (PoE): Yes | Switching capacity: 10 Gbit/s | Store-and-forward: Yes | Flow control support: Yes | Power over Ethernet plus (PoE+) ports quantity: 4 | Jumbo frames support: Yes | Depth: 98 mm | User guide: Yes | LED indicators: Yes | Loop protection: Yes | Product colour: Black | Auto MDI/MDI-X: Yes | Packet

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

buffer memory: 4 MB | Switch type: Managed | MAC address table: 8000 entries | Auto-negotiation: Yes | Port mirroring: Yes | Height: 25 mm | Power source: AC/DC | Wall mountable: Yes | Link aggregation: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Virtual LAN features: Tagged VLAN | Forwarding rate: 7.4 Mpps | Warnings: Do not open the case or try to repair it yourself. | Warnings: The product is not suitable for disposal in the regular waste bin. Take your used electronic equipment to a recycling centre in accordance with local regulations. | DC input voltage: 53.5 V | Cloud-managed: Yes | Warnings: Ensure the unit is adequately ventilated during operation. | Jumbo frames: 15 | Fanless: Yes | Transmission distance (max): 0.25 km | Virtual LAN features: Port-based VLAN | Virtual LAN features: MTU VLAN | Compliance certificates: Federal Communications Commission (FCC)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950