

Cudy RE1200 Outdoor Network repeater White 10, 100 Mbit/s



Model: AP1200 OUTDOOR

Manufacturer: CUDY

EAN: 6971690792855

Product Code: 613997

R2,077

A Wide-Range RE or Fit AP

Expand with AC1200 Wi-Fi

With MU-MIMO and dual-band features, the AC1200 Wi-Fi RE/AP can connect to over 30 devices while minimizing latency. The maximum number of simultaneous connections per AP/RE is 128 devices. No Standalone mode and requires a gateway in front of it.

Boosted Wi-Fi Coverage with Beamforming

Tested Wi-Fi coverage performance in four scenarios, achieved by Beamforming technology and two external antennas. If your space is too large for one access point to cover, you can expand your Wi-Fi coverage into a Mesh network by adding another Cudy RE/AP.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Works in Rain, Thunder, Dust, Heat, Cold

The RE/AP is protected by an IP65 standard case, shielding it from rain and dust when installed vertically. It also features 4 kV Lightning/Surge and 8 kV ESD protection for higher reliability in thunderstorms. Its working temperatures span from -40 °F to 149 °F (-40 °C to 65 °C).

Cudy Mesh Satellite

Seamless Roaming for Smooth Wi-Fi Experience

Enhance the Wi-Fi experience for your visitors by implementing a unified Wi-Fi name across your entire premises. Add this AP/RE behind a mesh router/AC, enjoy uninterrupted roaming as clients seamlessly connect to the strongest available Wi-Fi node without manual switching.

Plug-and-Play Mesh Installation

Simply Plug and Unplug for Mesh Setup

Connect the PoE adapter LAN port to a Cudy Mesh AP/router/AC to add the new RE/AP to the Mesh network. Feel free to unplug it or keep using Ethernet backhaul after pairing.

Leave the Rest to Adaptive Routing

Adaptive Routing improves the system's awareness of the capacity used by each node. Once the backhaul path is jammed by clients or interfered with by environmental factors, it will automatically switch to a better path for improved stability.

Guide to Wiring and Physical Installation

Ethernet Port with PoE

Adapter included for —

24 V Passive PoE (Adapter included, not waterproof)

Mounting Kit Included

A mounting kit is included in the box, supporting—

Wall-Mounting

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

