

Tenda TX2L Pro wireless router Gigabit Ethernet Dual-band (2.4 GHz 5 GHz) Black



Model: TX2L Pro

Manufacturer: TENDA

EAN: 6932849424201

Product Code: 621329

R816

AC input voltage: 100 - 240 V | Output voltage: 12 V | Output current: 1 A | Top Wi-Fi standard: Wi-Fi 6 (802.11ax) | USB port: No | DC-in jack: Yes | Depth: 56 mm | Ethernet LAN: Yes | Compliance certificates: Federal Communications Commission (FCC) | Supported network protocols: IPv4, IPv6 | AC adapter included: Yes | Compliance certificates: RoHS | Compliance certificates: CE | Ethernet LAN (RJ-45) ports: 4 | Operating temperature (T-T): 0 - 40 °C | Product colour: Black | Quick installation guide: Yes | Ethernet LAN data rates: 10 | Wi-Fi standards: 802.11a | Wi-Fi standards: Wi-Fi 6 (802.11ax) | Ethernet LAN interface type: Gigabit Ethernet | DHCP server: Yes | Wi-Fi standards: 802.11b | Wi-Fi standards: Wi-Fi 4 (802.11n) | Wi-Fi standards: 802.11g | Wi-Fi standards: Wi-Fi 5 (802.11ac) | VPN server: PPTP | Power source type: AC | Product type: Tabletop router | Reset button: Yes | Wi-Fi band: Dual-band (2.4 GHz / 5 GHz) | Height: 200 mm | Antenna design: External | Storage temperature (T-T): -40 - 70 °C | Cables included: LAN (RJ-45) | Ethernet LAN data rates: 100 Mbit/s |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Antennas quantity: 5 | AC input frequency: 50/60 Hz | Operating relative humidity (H-H): 10 - 90% | DHCP client: Yes | Ethernet LAN data rates: 1000 | DSL WAN: No | Cabling technology: 10/100/1000Base-T(X) | Width: 244 mm | Ethernet WAN: Yes | Storage relative humidity (H-H): 5 - 90% | WLAN data transfer rate (max): 1201 Mbit/s | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.3u | Web-based management: Yes | SIM card slot: No | Firewall: Yes | Dynamic DNS (DDNS): Yes | WLAN data transfer rate (second band): 1201 Mbit/s | Universal Plug and Play (UPnP): Yes | WPS push button: Yes | DMZ support: Yes | WLAN data transfer rate (first band): 300 Mbit/s | Parental control: Yes | 3G/4G USB modem compatibility: No

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950