

Switch UBIQUITI 180 Watts USW- PRO-MAX-16- POE



Model: USW-PRO-MAX-16-POE

Manufacturer: UBIQUITI

EAN: 810084694572

Product Code: 621352

R9,377

A 16-port, Layer 3 Etherlighting™ switch with 2.5 GbE, PoE++ output, and versatile mounting options.

- Etherlighting™ ports that illuminate to indicate port location, speed/link, and native VLAN/network
- (4) 2.5 GbE PoE++ ports
- (12) GbE PoE+ ports
- (2) 10G SFP+ ports
- 180W total PoE availability
- Versatile desktop, wall, and rack mounting
- Silent, fanless cooling system

Summary: Ubiquiti Pro Max 16 PoE. Switch type: Managed, Switch layer: L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

16. Switching capacity: 84 Gbit/s. Networking standards: IEEE 802.1x. DC input voltage: 44 - 57 V. Power connector: DC-in jack. Power over Ethernet (PoE). Rack mounting | Vendor Homepage: <https://eu.store.ui.com/eu/en/pro/category/switching-professional-max/products/usw-pro-max-16-poe> | Switch layer: L3 | Switch type: Managed | 2.5G Ethernet (copper) ports quantity: 4 | Basic switching RJ-45 Ethernet ports quantity: 16 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Gigabit Ethernet (copper) ports quantity: 12 | Power connector: DC-in jack | SFP+ module slots quantity: 2 | 10G support: Yes | Broadcast storm control: Yes | Flow control support: Yes | Networking standards: IEEE 802.1x | Port mirroring: Yes | Rate limiting: Yes | Virtual LAN features: Voice VLAN | VLAN support: Yes | Forwarding rate: 62.496 | Jumbo frames support: Yes | Switching capacity: 84 | Throughput: 42 | DHCP features: DHCP snooping/DHCPv6 relay | IGMP snooping: Yes | Loop protection: Yes | Multicast support: Yes | Display type: LCM | Housing material: Steel | LED indicators: System | Product colour: Grey | Rack mounting: Yes | Reset button: Yes | AC input frequency: 50/60 | AC input voltage: 100 - 240 | DC input voltage: 44 - 57 | Power consumption (max): 30 | Power source: AC/DC | Power supply included: Yes | Redundant power supply (RPS) support: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 15 | Power over Ethernet 4PPoE (PoE++) ports quantity: 4 | Power over Ethernet plus (PoE+) ports quantity: 12 | Total Power over Ethernet (PoE) budget: 180 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 40 | Depth: 160 | Height: 43.7 | Weight: 2100 | Width: 325.1 | Cables included: Power | Manual: Yes | Mounting brackets included: Yes | Compliance certificates: CE/Federal Communications Commission (FCC)/Industry Canada (IC) | Product Net Weight: 2.1 | Shipping Box Height: 25.5 | Unit Calculated Volume: 0.01723 | Unit Calculated Weight: 4.08 | Units per Shipping Box: 4 | Model: USW-PRO-MAX-16-POE | Model name: Pro Max 16 PoE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950