

Switch UBIQUITI USW-PRO-8-POE Type L3 2xSFP+ 8xRJ45 PoE+ ports 8 120 Watts USW-PRO- 8-POE



Model: USW-PRO-8-POE

Manufacturer: UBIQUITI

EAN: 810084692691

Product Code: 621660

R7,309

An 8-port, Layer 3 switch with PoE+ and PoE++ output.

- (6) GbE PoE+ ports
- (2) GbE PoE++ ports
- (2) 10G SFP+ ports
- 120W total PoE availability

Summary: Ubiquiti UniFi USW-PRO-8-POE. Switch type: Managed, Switch layer: L2/L3. Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

quantity: 8. Full duplex. Switching capacity: 56 Gbit/s. Networking standards: IEEE 802.3af, IEEE 802.3at. Power over Ethernet (PoE). Form factor: 1U | Vendor Homepage: <https://eu.store.ui.com/eu/en/products/usw-pro-8-poe> | Switch layer: L2/L3 | Switch type: Managed | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | SFP+ module slots quantity: 2 | 10G support: Yes | Auto MDI/MDI-X: Yes | Auto-sensing: Yes | Copper ethernet cabling technology: 100BASE-FX/100BASE-TX/10BASE-T/10BASE-TX | Flow control support: Yes | Full duplex: Yes | Half duplex: Yes | Link aggregation: Yes | Networking standards: IEEE 802.3af/IEEE 802.3at | Port mirroring: Yes | Spanning tree protocol: Yes | VLAN support: Yes | Jumbo frames support: Yes | Static route: Yes | Switching capacity: 56 | Throughput: 28 | Authentication: Port-based authentication | Authentication type: IEEE 802.1x,RADIUS | DHCP features: DHCP server | Form factor: 1U | Housing material: Metal/Plastic | LED indicators: Activity/Link/PoE/Speed/System | Product colour: White | AC input voltage: 100 - 240 | Input current: 2 | Number of power supply units: 1 | Power source: AC/DC | Power supply included: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) power per port: 60 | Power over Ethernet 4PPoE (PoE++) ports quantity: 2 | Power over Ethernet plus (PoE+) ports quantity: 6 | Total Power over Ethernet (PoE) budget: 120 | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -5 - 45 | Depth: 248 | Height: 44 | Weight: 2100 | Width: 200 | Manual: Yes | Sustainability compliance: Yes | Certification: CE, FCC, IC | Compliance certificates: CE/Federal Communications Commission (FCC) | Product Net Weight: 2.4 | Shipping Box Height: 28.5 | Unit Calculated Volume: 0.009386 | Unit Calculated Weight: 2.93 | Units per Shipping Box: 6 | Model name: USW-PRO-8-POE

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950