



D-Link DXS-1210-16TC/E network switch Managed L2 10G Ethernet (100/1000/10000) Grey

Model: DXS-1210-16TC/E

Manufacturer: D-LINK

EAN: 790069467660

Product Code: 642369

R40,406

Produktbeschreibung 10-Gigabit-Switches waren einmal ausschließlich großen Unternehmen vorbehalten. Jetzt machen die D-Link 10-Gigabit Ethernet Smart Managed Switches der DXS-1210-Serie den Nutzen von leistungstarkem 10G-Ethernet mit niedrigen Latenzzeiten für Unternehmen jeder Größe erschwinglich. Die DXS-1210-Switches sind eine kostengünstige Lösung, die eine Vielzahl von Netzwerkanforderungen in Unternehmen jeder Größe erfüllen kann. Mit Unterstützung für 10GBASE-T / SFP+-Combo-Ports bieten sie Flexibilität für das gesamte Netzwerk und erleichtern damit die Netzwerkintegration. Durch hohe Leistung und geringe Latenzzeiten erfüllen Sie die Ansprüche von Virtualisierung, Cloud-Diensten und Server-zu-Server-Anwendungen - perfekt für kleine bis mittlere Unternehmen. Art.-Nr.: 100019910 Typ: Switch | EAN: 0790069467660 | Hersteller-

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Nr.: DXS–1210–16TC/E | Bauform: Desktop | Einsatzbereich: Business | Anschlüsse: 12x (davon: 12x 1000/2500/5000/10000) | Routing & Switching: 200 GBit/s | LEDs: Activity, LAN-Link LEDs: 16x | Feature: MAC Address Table: Up to 32K entries, Static MAC Addresses: 128IGMP Snooping, IGMP v1/v2 Snooping, IGMP v3 awareness, Supports 384 IGMP groups, Supports at least 128 static multicast addresses, Per VLAN IGMP Snooping, Support host-based fast leave, MLD Snooping, MLD v1 Snooping, MLD v2 awareness, Support 384 groups, Support 128 static multicast addresses, Support host-based fast leave, LLDP, LLDP-MED, Spanning Tree Protocol, 802.1D STP, 802.1w RSTP, 802.1s MSTP, Flow Control, 802.3x Flow Control, HOL Blocking Prevention, Port Mirroring, One-to-One, Many-to-One, Supports Mirroring for Tx/Rx/Both, 802.3ad Link Aggregation: Maximum of 8 groups/8 ports per group, Jumbo Frame, Up to 10KB, Loopback Detection, ERPS (Ethernet Ring Protection Switching) | Gewicht: 4,6 kg

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950