

TP-Link 8-Port Gigabit Desktop Network Switch



Model: TL-SG1008D

Manufacturer: TP-LINK

EAN: 1210002616645

Product Code: 650094

R1,027

Certification: CE, FCC, RoHS | Package weight: 300 g | Operating relative humidity (H-H): 10 - 90% | Power consumption (max): 3.53 W | Power source: DC | Input current: 0.6 A | AC input voltage: 100 - 240 V | Power consumption (typical): 4.63 W | AC input frequency: 50/60 Hz | LED indicators: Yes | Package width: 110 mm | Width: 180 mm | Cables included: AC | Operating temperature (T-T): 0 - 40 °C | Ethernet LAN data rates: 10,100,480,800,1000 Mbit/s | Storage relative humidity (H-H): 5 - 90% | Package height: 85 mm | Power supply included: Yes | Networking standards: IEEE 802.3x | Power over Ethernet (PoE): No | Networking standards: IEEE 802.3i | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Harmonized System (HS) code: 85176990 | Storage temperature (T-T): -40 - 70 °C | Package depth: 185 mm | User guide: Yes | Housing material: Plastic | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Package type: Box | Full duplex: Yes | Height: 25.5 mm | Networking standards: IEEE 802.3u | Copper ethernet cabling technology: 100BASE-TX | Rack mounting: No | Basic switching RJ-45 Ethernet ports quantity: 8 | Product colour: Black | Fanless: Yes | DC input voltage: 9 V | AC adapter included: Yes | Copper ethernet cabling technology: 10BASE-T | Heat dissipation: 15.8 BTU/h | Switch type: Unmanaged | 10G support: No | Packet forwarding rate (100 Mbps): 148800 pps |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Copper ethernet cabling technology: 1000BASE-T | Flow control support: Yes | Stackable: No | Depth: 90 mm | Packet forwarding rate (1 Gbps): 14880 pps | Packet forwarding rate (10 Mbps): 1488000 pps | Cable types supported: Cat3 | Wall mountable: Yes | Packet buffer memory: 2 MB | Auto-negotiation: Yes | MAC address table: 4000 entries | Jumbo frames support: Yes | Jumbo frames: 15000 | Store-and-forward: Yes | Power connector: DC-in jack | Switching capacity: 16 Gbit/s | Compliance certificates: RoHS | Compliance certificates: CE | Cable types supported: Cat4 | Compliance certificates: Federal Communications Commission (FCC) | Gigabit Ethernet (copper) ports quantity: 8 | Cable types supported: Cat5 | Cable types supported: Cat5e | Maximum cable length: 100 m | Auto MDI/MDI-X: Yes | Sustainability compliance: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950