

TP-Link 8-Port Gigabit Easy Smart Switch with 4-Port PoE



Model: TL-SG108PE

Manufacturer: TP-LINK

EAN: 1210002616942

Product Code: 650095

R1,698

Certification: FCC, CE, RoHS | Store-and-forward: Yes | Gigabit Ethernet (copper) ports quantity: 8 | Jumbo frames support: Yes | Storage relative humidity (H-H): 5 - 95% | Total Power over Ethernet (PoE) budget: 64 W | Jumbo frames: 15000 | Rate limiting: Yes | Link aggregation: Yes | LED indicators: Link | Package width: 131 mm | LED indicators: Speed | Package type: Box | Package height: 121 mm | Operating temperature (T-T): 0 - 40 °C | LED indicators: Power | Heat dissipation: 256.19 BTU/h | LED indicators: Activity | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Broadcast storm control: Yes | Networking standards: IEEE 802.3ab | Networking standards: IEEE 802.1p | Power over Ethernet (PoE) power per port: 15.4 W | Basic switching RJ-45 Ethernet ports quantity: 8 | AC input voltage: 220 V | Cable types supported: Cat3 | LED indicators: Status | Cable types supported: Cat4 | Cable types supported: Cat6 | Switch layer: L2 | Input current: 1.25 A | Web-based management: Yes | Cable types supported: Cat5 | Cable types supported: Cat5e | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.3i | Power source: DC | Power supply included: Yes | LED indicators: PoE | Loop protection: Yes | Networking standards: IEEE 802.1Q | Networking standards: IEEE 802.3x | VLAN support: Yes | AC input frequency: 50 Hz | Power

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

over Ethernet (PoE) ports quantity: 4 | Operating relative humidity (H-H): 10 - 90% | Switch type: Managed | Harmonized System (HS) code: 85176990 | IGMP snooping: Yes | Number of VLANs: 32 | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | 10G support: No | Input voltage: 48 V | Width: 158 mm | Package depth: 196 mm | User guide: Yes | Depth: 101 mm | Packet forwarding rate (1 Gbps): 11900000 pps | Power over Ethernet (PoE): Yes | Port mirroring: Yes | MAC address table: 4000 entries | Product colour: Black | Auto MDI/MDI-X: Yes | Packet buffer memory: 1.5 MB | Package weight: 860 g | Auto-negotiation: Yes | Cables included: AC | Height: 25 mm | Power consumption (max): 65.2 W | Virtual LAN features: Port-based VLAN | Power over Ethernet plus (PoE+) ports quantity: 4 | Forwarding rate: 11.9 Mpps | Switching capacity: 16 Gbit/s

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950