

TP-Link Omada 52-Port Gigabit L2+ Managed Switch with 48- Port PoE+



Model: TL-SG3452P

Manufacturer: TP-LINK

EAN: 1210002611947

Product Code: 650096

R13,881

Rack mounting: Yes | Width: 440 mm | Power over Ethernet (PoE): Yes | Power source: AC |
Networking standards: IEEE 802.3ad | Networking standards: IEEE 802.1s | Networking standards:
IEEE 802.1w | Ethernet LAN data rates: 10,100,1000 Mbit/s | Storage temperature (T-T): -40 - 70 °C |
Quality of Service (QoS) support: Yes | LED indicators: Yes | AC input voltage: 100 - 240 V | Power
consumption (max): 464.2 W | Reset button: Yes | Total Power over Ethernet (PoE) budget: 384 W |
Height: 44 mm | Quick start guide: Yes | Networking standards: IEEE 802.1p | Web-based
management: Yes | Networking standards: IEEE 802.3x | Form factor: 1U | Operating temperature (T-
T): 0 - 40 °C | Storage relative humidity (H-H): 5 - 90% | Power over Ethernet (PoE) power per port:
30 W | Cables included: AC | Product colour: Black | Operating relative humidity (H-H): 10 - 90% | AC
input frequency: 50/60 Hz | Package type: Box | Networking standards: IEEE 802.1D | Number of
fans: 3 fan(s) | Depth: 330 mm | Manual: Yes | Power supply included: Yes | Switching capacity: 104
Gbit/s | VLAN support: Yes | Basic switching RJ-45 Ethernet ports quantity: 48 | Password protection:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Yes | SFP module slots quantity: 4 | Jumbo frames support: Yes | Management protocols: SNMPv1/v2c/v3, SNTP | Forwarding rate: 77.38 Mpps | GARP VLAN Registration Protocol (GVRP): Yes | Packet buffer memory: 12 MB | Rate limiting: Yes | Link aggregation: Yes | Switch layer: L2/L3 | DHCP features: DHCPv6 client | Console port: RJ-45/micro-USB | Cloud-managed: Yes | IP routing: Yes | DHCP features: DHCPv6 snooping | Access Control List (ACL): Yes | DHCP features: DHCP snooping | Port mirroring: Yes | System event log: Yes | Heat dissipation: 1584.08 BTU/h | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Broadcast storm control: Yes | DHCP features: DHCP server | DHCP features: DHCP client | DHCP features: DHCP relay | Store-and-forward: Yes | ARP inspection: Yes | MIB support: Yes | Power connector: AC-in jack | MAC address table: 16000 entries | IGMP snooping: Yes | Loop protection: Yes | Virtual LAN features: Voice VLAN | Power over Ethernet plus (PoE+) ports quantity: 48 | Number of static routes: 48 | Policy-based routing: Yes | Spanning tree protocol: Yes | Jumbo frames: 9000 | Virtual LAN features: Tagged VLAN | Virtual LAN features: Private VLAN | Static route: Yes | Switch type: Managed | Active link detection: Yes | Virtual LAN features: Protocol-based VLAN | Head-of-line (HOL) blocking: Yes | BPDU filtering/protection: Yes | Multicast support: Yes | Virtual LAN features: MAC address-based VLAN | Flow control support: Yes | Authentication: MAC-based authentication, Port-based authentication | 10G support: No | SSH/SSL support: Yes | Number of VLANs: 4000

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950