

TP-Link 18-Port Gigabit Rackmount Switch with 16 PoE+



Model: TL-SG1218MP

Manufacturer: TP-LINK

EAN: 1210002617086

Product Code: 650097

R4,571

Certification: CE, FCC, RoHS | Operating relative humidity (H-H): 10 - 90% | Networking standards: IEEE 802.3u | Networking standards: IEEE 802.1Q | Storage relative humidity (H-H): 5 - 90% | Full duplex: Yes | Networking standards: IEEE 802.3 | Networking standards: IEEE 802.3ab | Package height: 80 mm | AC input voltage: 100 - 240 V | Heat dissipation: 977.44 BTU/h | Height: 44 mm | Traffic classification: Yes | Width: 440 mm | Packet buffer memory: 4.1 MB | Half duplex: Yes | Power over Ethernet (PoE) power per port: 30 W | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Package weight: 3.05 kg | Cables included: AC | Gigabit Ethernet (copper) ports quantity: 18 | Networking standards: IEEE 802.1p | Auto MDI/MDI-X: Yes | Rack mounting: Yes | Ethernet LAN data rates: 10,100,1000 Mbit/s | Cable types supported: Cat6 | AC input frequency: 50 - 60 Hz | Basic switching RJ-45 Ethernet ports quantity: 18 | LED indicators: Yes | Harmonized System (HS) code: 85176990 | Cable types supported: Cat5 | Cable types supported: Cat5e | Number of fans: 2 fan(s) | Package width: 250 mm | Power supply included: Yes | MAC address table: 8000 entries |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Auto-negotiation: Yes | Power consumption (max): 286.64 W | Power over Ethernet plus (PoE+) ports quantity: 16 | Switch type: Unmanaged | Combo SFP ports quantity: 2 | MAC address auto-aging supported: Yes | Networking standards: IEEE 802.3x | Jumbo frames support: Yes | Package depth: 528 mm | 10G support: No | Depth: 180 mm | Form factor: 1U | Power over Ethernet (PoE): Yes | Storage temperature (T-T): -40 - 70 °C | Quality of Service (QoS) support: Yes | Jumbo frames: 10000 | Cable types supported: Cat3 | Housing material: Metal | Product colour: Black | Power source: AC | Cable types supported: Cat4 | MAC address auto-learning supported: Yes | Quick start guide: Yes | Switching capacity: 36 Gbit/s | Forwarding rate: 26.78 Mpps | Operating temperature (T-T): 0 - 50 °C | Total Power over Ethernet (PoE) budget: 250 W | Flow control support: Yes

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950