

Ubiquiti Dream Machine Pro Max gateway/controller 10, 100, 1000, 2500 Mbit/s



Model: UDM-Pro-Max

Manufacturer: UBIQUITI

EAN: 810084693254

Product Code: 664616

R13,998

Processor manufacturer: ARM | Heat dissipation: 205 BTU/h | DC input voltage: 12 V | Height: 43.7 mm | Routing protocols: BGP | LED indicators: Activity | LED indicators: Ready | Ethernet LAN data rates: 10 | Input current: 2 A | Input voltage: 100 - 240 V | Power over Ethernet (PoE): No | SSD capacity: 128 GB | Routing protocols: OSPF | Width: 442.4 mm | Operating temperature (T-T): -10 - 40 °C | Ethernet LAN (RJ-45) ports: 9 | LED indicators: Error | LED indicators: Link | Quality of Service (QoS) support: Yes | Product colour: Grey | Mounting type: Rack mounting | Input frequency: 50/60 Hz | Internal memory: 8000 MB | Rack capacity: 1U | Operating relative humidity (H-H): 5 - 95% | Depth: 285.6 mm | Reset button: Yes | Processor model: Cortex-A57 | Control display unit: Yes | VLAN support: Yes | Ethernet LAN data rates: 100 Mbit/s | Processor frequency: 2000 MHz | Multicast support: Yes | Ethernet LAN data rates: 1000 | Firewall security: Yes | DHCP server: Yes | Processor family: ARM Cortex | Ethernet LAN data rates: 2500 Mbit/s | Number of processors installed: 1 |

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Cables included: AC | Built-in processor: Yes | Weight: 4.7 kg | Power consumption (max): 60 W |
Display type: LCM | Flash memory: 32000 MB | WAN connection: Ethernet (RJ-45), SFP+ |
Electrostatic Discharge (ESD) protection (air): 15 kV | Electromagnetic (EMP) protection: Yes | Port
aggregation: Yes | Electrostatic Discharge (ESD) protection (contact): 8 kV | SFP+ ports quantity: 2 |
Electromagnetic (EMP) protection (air): 15 kV | Warnings: Make sure the unit is stably mounted and
ventilated. | Warnings: Do not use in damp conditions. | Warnings: Do not open the appliance - risk
of electric shock. | Electromagnetic (EMP) protection (contact): 8 kV | Compliance certificates:
National Defense Authorization Act (NDAA) | Compliance certificates: Industry Canada (IC) |
Compliance certificates: CE | Compliance certificates: Federal Communications Commission (FCC) |
Enclosure material: Aluminium/SGCC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950