

InLine 57885A video switch HDMI



Model: 57885A

Manufacturer: INLINE

EAN: 4043718344246

Product Code: 710979

R3,206

Ultra HD perfection: Supports 8K@60Hz and 4K@120Hz for impressive picture quality in home cinema and professional AV applications.

Versatile audio output: Choose between HDMI (audio only), optical (SPDIF) or analogue (3.5 mm jack) – ideal for modern and classic audio systems.

eARC, CEC and EDID for optimal integration: Maximum compatibility with modern AV receivers and automatic control via HDMI connections.

Manual and automatic switching: Flexible control via IR remote control or directly on the device – for maximum ease of use.

Future-proof with HDMI 2.1 and HDCP 2.3: Best performance with maximum compatibility – even for upcoming video and audio formats.

The InLine HDMI Switch 4-way with audio decoupling brings high-end connectivity and maximum flexibility to your AV setup. It allows you to connect up to four HDMI sources to a single display with eARC support – ideal for home cinema enthusiasts, gamers or professional AV installations.

With support for video resolutions up to 8K@60Hz (4:2:0, 12-bit) and 4K@120Hz (4:4:4, 12-bit), you'll

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

experience crystal-clear images with rich colour depth. The switch processes modern colour spaces and HDR formats such as HDR10, Dolby Vision and HLG to reproduce every detail faithfully.

A special highlight is the audio extraction: in addition to HDMI audio only, the device also offers outputs for optical SPDIF and analogue stereo output via 3.5 mm jack. This allows both modern AV receivers and classic sound systems to be connected without any problems. Control is convenient via the supplied IR remote control or directly via the keypad on the device.

Thanks to eARC and CEC support as well as switchable EDID modes (2.0 / 5.1 / 7.1 / PASS), the switch adapts flexibly to your audio and video environment. Automatic source switching can be deactivated if required. A USB-C port enables firmware updates and ensures long-term compatibility with new standards.

The robust metal housing ensures durability, while ESD protection, an external plug-in power supply with lock and well-designed connection options facilitate professional installations.

Inputs: 4 × HDMI IN (Type A, 19-pin)

Outputs

- 1 × HDMI OUT 1 (eARC, Type A)
- 1 × HDMI OUT 2 (AUDIO ONLY, Type A)
- 1 × optical (SPDIF)
- 1 × L/R (3.5 mm jack)

Video resolution

- up to 8K@60Hz (4:2:0, 12 bits)
- 4K@120Hz (4:4:4, 12 bits),
- incl. 720p, 1080p, 4K@30/60/100/120Hz, 8K@24/30/50Hz

Video bandwidth: 48 Gbps (FRL) / 18 Gbps (TMDS)

HDMI version: 2.1

HDCP version: 2.3

Colour spaces: RGB, YCbCr 4:4:4 / 4:2:2 / 4:2:0

Colour depth: 8 / 10 / 12 bits

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

Audio formats (HDMI): LPCM 2.0–7.1, Dolby Digital, Dolby Digital Plus, Dolby TrueHD, Dolby Atmos, DTS, DTS-HD, DTS:X

Audio formats (SPDIF): LPCM 2.0, Dolby Digital, Dolby Digital Plus, DTS

Audio formats (L/R): PCM 2.0

Control: Front buttons, IR remote control, CEC

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Auto switching: Can be enabled/disabled
EDID: 2.0 / 5.1 / 7.1 / PASS (switchable)
Service port: USB-C for firmware update
ESD protection: ± 8 kV air / ± 4 kV contact
Dimensions: 200 × 84 × 20 mm
Weight: 430 g
Housing: metal, black
Operating temperature: 0–40 °C
Storage temperature: –20–60 °C
Humidity: 20–80% operating / 10–90% storage (non-condensing)

External power supply (power adapter)

Type: External plug-in power adapter with lock
Input voltage: 100–240 V AC, 50/60 Hz
Output voltage: 5.0 V DC
Output current: max. 1.0 A
Output power: 5.0 W
Average efficiency during operation: 79.70%
Efficiency at low load (10%): 76.78%
Power consumption at zero load: 0.092 W

Scope of delivery

1 × InLine® HDMI switch, 4-way, 48 Gb/s, 8K@60Hz, with audio decoupling
1 × power supply unit (5 V/1 A)
1 × IR remote control
1 × user manual in German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950