



InLine 57885C KVM switch Rack mounting Black



Model: 57885C

Manufacturer: INLINE

EAN: 4043718344260

Product Code: 710981

R3,264

Two PCs, one workspace:Control two computers with just one mouse, keyboard and HDMI display – ideal for the office and home office.

Highest image quality up to 8K@60Hz:HDMI 2.1 with Dolby Vision, HDR10+ and 4K@144Hz – brilliant display even for gaming or image editing.

USB 3.2 Gen.1 sharing with 5 Gb/s:Use printers, storage devices or webcams on both PCs – without switching cables.

Versatile control options:Switch via button, hotkey, IR remote control or RS-232 – full control in any environment.

Professional signal management:No audio/video lag, HDCP 2.3, CEC and ESD protection – reliable in IT and server structures.

The InLine KVM Switch 2-way with HDMI 2.1 connects two computers with just one monitor, one keyboard and one mouse – ideal for professional IT environments, home offices or training rooms. It allows easy switching between both PCs and supports resolutions up to 8K at 60 Hz, 4K at 144 Hz

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

and modern HDR standards such as Dolby Vision and HDR10+.

In addition to video and audio, four USB 3.2 Gen.1 ports allow peripheral devices such as printers, cameras or external drives to be shared. Switching between the two systems can be done via front buttons, hotkeys on the keyboard, an IR remote control or an RS-232 interface – for maximum flexibility in control.

The KVM switch supports all common audio formats including Dolby Atmos and DTS-HD. Thanks to HDMI 2.1, HDCP 2.3, CEC, robust construction and high ESD protection, the device is not only powerful but also particularly reliable in continuous use. A comprehensive accessory package with HDMI and USB cables, power supply, RS-232 connector and mounting material is included in the scope of delivery.

HDMI inputs: 2 × HDMI (type A, 19-pin)

HDMI output: 1 × HDMI (type A, 19-pin)

Video resolution: up to 8K@60 Hz, 4K@120 Hz/144 Hz, 1080P@240 Hz

HDR support: HDR, HDR10, HDR10+, Dolby Vision, HLG

HDMI standard: HDMI 2.1

HDCP compatibility: HDCP 2.3

Colour spaces: RGB, YCbCr 4:4:4 / 4:2:2 / 4:2:0

Colour depth: 8, 10, 12 bits

Video/audio latency: none

CEC support: yes

Audio formats HDMI IN/OUT: LPCM, Dolby Digital/Plus/EX, Dolby TrueHD, Dolby Atmos, DTS, DTS-EX, DTS-96/24, DTS High Res, DTS-HD Master Audio, DTS:X, DSD

Audio output L/R: PCM 2.0CH (3.5 mm stereo)

USB ports: 4 × USB 3.2 Gen.1 (USB-A), 2 × USB Host (USB-B)

Supported USB speeds: USB 3.2 Gen.1 (with hotkey OFF), USB 1.1 (with hotkey ON)

RS-232: 3-pin terminal connection

IR EXT: 3.5 mm jack socket (38 kHz)

Dimensions: 175 × 100 × 30 mm

Weight: 506 g

Housing: metal, black

Operating ambient temperature: 0–40 °C

Storage ambient temperature: –20–60 °C

Humidity: 20–90 % RH (non-condensing)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

ESD protection: ± 8 kV air / ± 4 kV contact

Recommended HDMI cable lengths

Up to 2 m: 8K / 4K@120Hz

Up to 5 m: Ultra HDMI 2.1

Up to 10 m: 1080p with standard cable

External power supply (power adapter)

Type: External plug-in power adapter with lock

Input voltage: 100–240 V AC, 50/60 Hz

Output voltage: 12.0 V DC

Output current: max. 1.0 A

Output power: 12.0 W

Average efficiency in operation: 85.23%

Efficiency at low load (10%): 78.53%

Power consumption at zero load: 0.09 W

Contents of delivery

1 × InLine® KVM switch, 2-port, HDMI, 8K60Hz

1 × IR remote control

1 × IR receiver cable (1.5 m, 38 kHz)

2 × HDMI cable (1.5 m)

2 × USB 3.2 Gen.1 cables (1.8 m, USB-A to USB-B)

1 × 12 V/1 A power supply with lock

1 × 3-pin terminal connection plug

2 × mounting brackets

4 × screws (KM3×4)

1 × user manual in German/English

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950