

iiyama ProLite XUB2797HSN- W2 computer monitor 68.6 cm (27) 1920 x 1080 pixels Full HD LED White



Model: XUB2797HSN-W2

Manufacturer: IIYAMA

EAN: 4948570124992

Product Code: 721760

R4,504

Packaging content: quick start guide, safety guide | Manufacturer warranty: 5 years (for details and eligible countries please check the Warranty section of our website) | Cable lock slot: Yes | Depth (with stand): 209.5 mm | Display diagonal: 68.6 cm (27") | Contrast ratio (dynamic): 80000000:1 | DisplayPorts quantity: 1 | Response time: 1 ms | Ethernet LAN (RJ-45) ports: 1 | Display resolution: 1920 x 1080 pixels | AC input frequency: 50/60 Hz | Weight: 6 kg | Pixel pitch: 0.311 x 0.311 mm | Native aspect ratio: 16:9 | Display number of colours: 16.7 million colours | Horizontal scan range: 30 - 110 kHz | AC input voltage: 100 - 240 V | Screen shape: Flat | Height (with stand): 550.5 mm | Display brightness (typical): 300 cd/m² | Tilt angle range: 5 - 23° | HDCP: Yes | Viewing angle, vertical: 178° | Product colour: White | Viewing angle, horizontal: 178° | Power consumption (off): 0.3

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

W | Package width: 679 mm | Package weight: 8.7 kg | HD type: Full HD | Cable lock slot type: Kensington | Width (with stand): 611.5 mm | Display surface: Matt | Warnings: Do not disassemble the monitor casing to avoid risk of electric shock. | Warnings: Unplug the monitor from the power source before cleaning. | Adjustable height (max): 15 cm | Warnings: Place the monitor on a flat and stable surface to avoid tipping and damage. | Number of downstream ports: 4 | Response time (MPRT): 1 ms | VESA Adaptive Sync support: Yes | Low Blue Light technology: Yes | NTSC coverage (typical): 72% | USB Power Delivery up to: 65 W | Control panel: Power, Menu, Adjustment/Volume, Adjustment/Shortcut Menu, Input/Exit | Depth (without stand): 209.5 mm | Swivelling: Yes | On Screen Display (OSD): Yes | Built-in USB hub: Yes | Colour gamut standard: NTSC | Contrast ratio (typical): 1000:1 | Colour gamut standard: sRGB | RMS rated power: 4 W | Panel mounting interface: 100 x 100 mm | Width: 611.5 mm | HDMI version: 1.4 | Display diagonal (metric): 68.6 cm | Depth: 209.5 mm | Power consumption (standby): 22 W | Flicker-free technology: Yes | Power consumption (typical): 22 W | Viewable size, vertical: 33.6 cm | VESA mounting: Yes | Power supply type: Internal | Package depth: 130 mm | Display technology: LED | USB hub version: 3.2 Gen 1 (3.1 Gen 1) | HDMI: Yes | Height adjustment: Yes | Maximum refresh rate: 100 Hz | Ethernet LAN: Yes | Built-in camera: No | Tilt adjustment: Yes | HDMI ports quantity: 1 | DDC/CI: Yes | European Product Registry for Energy Labelling (EPREL) code: 2035009 | Swivel angle range: -60 - 60° | Panel type: IPS | Width (without stand): 611.5 mm | DisplayPort out version: 1.2 | USB Power Delivery (USB PD): Yes | Package height: 427 mm | AMD FreeSync: Yes | Height (without stand): 400.5 mm | USB upstream port type: USB Type-C | Number of speakers: 2 | Cables included: USB Type-C | Weight (with stand): 6 kg | Compliance certificates: RoHS | Compliance certificates: CE | DisplayPort out quantity: 1 | Compliance certificates: UKCA | Compliance certificates: EAC | Compliance certificates: VCCI | Headphone out: Yes | Compliance certificates: WEEE | Built-in speaker(s): Yes | Viewable size, horizontal: 59.8 cm | Pivot: Yes | Compliance certificates: PSE | Market positioning: Business | Compliance certificates: REACH | Cables included: HDMI | Cables included: AC | Compliance certificates: TÜV mark | On Screen Display (OSD) languages: English | On Screen Display (OSD) languages: German | On Screen Display (OSD) languages: Italian | On Screen Display (OSD) languages: Dutch | Pivot angle: 0 - 90° | On Screen Display (OSD) languages: Japanese | Touchscreen: No | On Screen Display (OSD) languages: French | On Screen Display (OSD) languages: Spanish | On Screen Display (OSD) languages: Polish | On Screen Display (OSD) languages: Russian | On Screen Display (OSD) languages: Czech | Energy efficiency scale: A to G | sRGB coverage (typical): 99% | Cable management: Yes | Energy consumption (SDR) per 1000 hours: 21.6 kWh | Energy efficiency class (HDR): Not available | Energy efficiency class (SDR): E | Sustainability certificates: TCO | Sustainability certificates: ErP | Number of USB Type-C upstream ports quantity: 1

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

| Warranty period: 5 year(s)

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950