

AG Neovo TX- 2401 computer monitor 60.5 cm (23.8") 1920 x 1080 pixels Full HD LED Touchscreen Tabletop White



Model: TX2410A1E0100

Manufacturer: AG NEOVO

EAN: 4710739597554

Product Code: 763622

R26,714

The TX-2401 White touch screen monitor adopts PCAP multi-touch technology that is relatively unaffected by surface contaminants and allows 10-point multi-touch capabilities, offering an accurate and responsive touch experience. It is even responsive to latex gloves. Featuring a medical-grade power supply and versatile connectivity (e.g., DisplayPort, HDMI, and VGA inputs), the TX-2401 White is built for flexible use, such as patient check-in, patient queue management, medical research laboratories, or medical computer carts. The monitor is complemented by front IP65 and IK08 ratings, white metal casing, and an edge-to-edge 7H tempered glass overlay, ensuring durability and easy cleaning for continuous operation in healthcare environments.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

10-POINT PCAP TOUCH SCREEN

The TX-2401 White touch screen adopts PCAP touch technology with 10-point multi-touch capabilities that are unaffected by contamination, offering a fast, accurate, and responsive touch experience. The seamless touch experience is identical to that of smartphones and tablets, and is even responsive to latex gloves.

ENHANCED SAFETY WITH MEDICAL-GRADE POWER SUPPLY

Compliance with the IEC / EN 60601-1 standard power supply ensures the safety of your staff and patients in clinical settings, preventing electric shocks, as well as energy-related and heat-related hazards.

EASY TO MAINTAIN FOR NON-STOP USE

A commercial-grade panel, high-quality components and 7H scratch-resistant tempered glass screen ensure the display can be 24/7 constant used. Additionally, the screen is resistant to chemical disinfectants like alcohol for frequent cleaning.

FRONT IP65 DUST AND WATER PROTECTION

The TX-2401 White multi-touch monitor with a front-sided IP65 rating is designed to protect from dust and liquid spills, making it ideal for high-use public locations.

HIGH IMPACT-RESISTANT AGAINST VANDALISM

The touch display with an IK08 rating and metal casing prevents damage from impacts or acts of vandalism in high-traffic areas, ensuring a long service life.

MULTIPLE LAYOUTS FOR PUBLIC ACCESS

Thanks to VESA compatibility, the TX-2401 White offers flexible mounting options, such as desk mounting, attaching to a monitor arm, or integrating into a medical cart. The included ergonomic stand allows for a significant -2 to 180 degrees of tilt adjustment, facilitating additional flexibility when using. The display features 178 degrees of wide viewing angles to provide consistent colour performance for better viewing.

VERSATILE CONNECTIVITY

The TX-2401 White provides maximum versatility and enables users to connect to their own devices, such as a high-performance PC or media player, using the DisplayPort, HDMI, or VGA inputs.

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

CABLE MANAGEMENT

A specially designed monitor stand with integrated cable management keeps cables organized, prevents them from interfering when adjusting the screen up or down, and provides a clutter-free space.

SEAMLESS INTEGRATION

Touch support works with various operating systems, compatible with Windows, Linux, macOS, and certain Android versions. This enables more choice of the operating system you use.