



Access Point MIKROTIK 867 Mbps 2x10Base- T 100Base-TX 1000Base-T RBCAPGI- 5ACD2ND-XL

Model: RBCAPGI-5ACD2ND-XL

Manufacturer: MIKROTIK

EAN: 4752224007278

Product Code: 771990

R2,509

The ceiling AP on steroids! Our bestseller cAP is back – juiced up and stronger than ever. Compared to the previous cAP models, the improved high-gain antenna increases the covered area by up to 100%!

Need a nice-looking access point that won't get in your way? Or perhaps you're managing the network in a crowded place and don't want everyone to have physical access to the device? Either way – ceiling is the answer! The device itself is pretty sleek - the low profile attracts less attention than a smoke detector. Your clients, guests, or colleagues won't even notice it. But they will

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

definitely notice the blazing fast wireless connection all across the premises.

The new design features a larger high-gain antenna, higher sensitivity, and a built-in reflector. These improvements allow increasing the covered area by up to 100%, compared to the previous cAP models!

The dual-band, dual-chain 2.4 and 5 GHz wireless radio provides a strong coverage in 360 degrees around it, so you don't have to worry about the placement of the device so much. Putting it on the ceiling eliminates many signal absorption problems, such as the signal being blocked by large TV sets, metal cubicle walls in open space offices, etc.

Even though the radio supports repeater mode, the two Gigabit Ethernet ports give you the ability to extend your network with cables, even if PoE power is required: the cAP XL ac supports 802.3af/at PoE input on the first port and passive PoE output (up to 57V) on the second port.

Summary: Mikrotik cAP XL ac. 2.4 GHz, 5 GHz, Maximum data transfer rate: 867 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 24 W | Vendor Homepage: https://mikrotik.com/product/cap_xl_ac#fndtn-specifications | 2.4 GHz: Yes | 5 GHz: Yes | 6 GHz: No | Maximum data transfer rate: 867 | Maximum data transfer rate (2.4 GHz): 300 | Maximum data transfer rate (5 GHz): 867 | Wi-Fi data rate (max): 867 | Ethernet LAN data rates: 10/100/1000 | Frequency band: 2 - 5.5 | Networking standards: IEEE 802.3af/IEEE 802.3at | Cabling technology: 10/100/1000Base-T(X) | Bluetooth: No | Transmitting power (CE): 26 | Mean time between failures (MTBF): 100000 | Security features: IPsec hardware acceleration | Ethernet LAN (RJ-45) ports: 2 | DC-in jack: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | AC input voltage: 17 - 57 | DC voltage range: 24 | Input current: 1.2 | Power consumption (typical): 11 | Power consumption (max): 24 | Placement: Ceiling,Wall | Product colour: White | WPS push button: Yes | Antenna type: Internal | Chipset: IPQ-4018 | Built-in processor: Yes | Processor model: IPQ4018 | Processor frequency: 716 | Flash memory: 128 | Internal memory: 16 | Operating system installed: RouterOS | Security update term: IPsec hardware acceleration | Compliance certificates: CE/Federal Communications Commission (FCC)/RoHS | Width: 191 | Height: 42 | Wireless technology: Wi-Fi 5 | Warranty period: 5 | Unit Calculated Weight: 0.94 | Product Net Weight: 0.7 | Unit Calculated Volume: 0.004492 | Units per Shipping Box: 10 | Unit Width: 23.5 | Units per Pallet: 0 | Shipping Box Height: 33 | Unit Depth: 31.5 | Unit Height: 5 | Name: WRL ACCESS POINT 5GHZ/RBCAPGI-5ACD2ND-XL MIKROTIK | Model name:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

[shop.cssi.co.za](mailto:sales@cssi.co.za) | sales@cssi.co.za | +27 (11)541-9950

