

Access Point MIKROTIK 1200 Mbit/s LHG-5AXD

Model: LHG-5AXD

Manufacturer: MIKROTIK

EAN: 4752224009654

Product Code: 772006

R2,490

Need a fast, stable connection across large distances? Whether you’re bridging two buildings, connecting a remote site, or sharing your internet with nearby infrastructure — the new LHG Wi-Fi 6 series is built for the challenge. And here’s the best part: we’ve kept the same pricing as the previous generation. High performance, long range, and Wi-Fi 6 — all without breaking the budget.

The 802.11ax standard brings crucial improvements for long-distance wireless links — including better spectral efficiency, higher modulation rates (1024-QAM), and lower latency. That means stronger performance even in noisy environments and faster, more stable connections over a greater distance. Combined with WPA3 encryption and RouterOS v7, the LHG ax series is ready for the challenges of modern outdoor networking. Order yours today — and be ready too!

LHG 5 ax is compact, long-range CPE with a 24.5 dBi antenna. Perfect for links up to 20 km in most scenarios. Check related devices below for the XL version if you need a longer distance!

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Summary: Mikrotik LHG 5 ax. 5 GHz, Maximum data transfer rate: 1200 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 5 W | Vendor Homepage: https://mikrotik.com/product/lhg_5_ax#fndtn-gallery | 2,4 GHz: Ne | 5 GHz: Taip | Didžiausias duomenų perdavimo greitis: 1200 | Eterneto LAN duomenų perdavimo norma: 10/100/1000 | Tinklo standartai: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11n | Persiuntimo galia: 24 | Imtuvo jautrumas: -96, -80, -75, -70, -67 | DC įėjimo lizdas: Taip | Maitinimas per Eternetą (PoE): Taip | Palaikomas maitinimo per eternetą (en. PoE) tipas: Passive PoE | Galios suvartojimas (maks.): 5 | Talpinimo: Stulpas | Produkto spalva: Balta | Antenos tipas: Vidinis | Antenos stiprinimo lygis (max): 24.5 | Integruotas procesorius: Taip | Flash atmintis: 128 | Vidinė atmintis: 256 | Sertifikavimas: CE, FCC, IC, EAC, ROHS | Kiekis pakuotėje: 1 | Pridėtas PoE adapteris: Taip | Montavimo rinkinys: Taip | Darbo temperatūros diapazonas (TT): -40 - 70 | Bruto svoris: 10.8 | Neto svoris: 6 | Vienetų skaičius vienoje siuntimo dėžėje: 1 | Vieneto plotis: 48 | Vienetų skaičius ant paletės: 0 | Shipping Box Height: 47 | Vieneto gylis: 77 | Vieneto aukštis: 47 | Name: WRL LHG WIFI6/LHG-5AXD MIKROTIK | Model: LHG-5AXD | Model name: LHG 5 ax

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.
shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950