

Access Point MIKROTIK 1200 Mbit/s LHG- 5AXD



Model: LHG-5AXD

Manufacturer: MIKROTIK

EAN: 4752224009654

Product Code: 772006

R2,411

Need a fast, stable connection across large distances? Whether you're bridging two buildings, connecting a remote site, or sharing your internet with nearby infrastructure — the new LHG Wi-Fi 6 series is built for the challenge. And here's the best part: we've kept the same pricing as the previous generation. High performance, long range, and Wi-Fi 6 — all without breaking the budget.

The 802.11ax standard brings crucial improvements for long-distance wireless links — including better spectral efficiency, higher modulation rates (1024-QAM), and lower latency. That means stronger performance even in noisy environments and faster, more stable connections over a greater distance. Combined with WPA3 encryption and RouterOS v7, the LHG ax series is ready for the challenges of modern outdoor networking. Order yours today — and be ready too!

LHG 5 ax is compact, long-range CPE with a 24.5 dBi antenna. Perfect for links up to 20 km in most scenarios. Check related devices below for the XL version if you need a longer distance!

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Summary: Mikrotik LHG 5 ax. 5 GHz, Maximum data transfer rate: 1200 Mbit/s, Ethernet LAN data rates: 10,100,1000 Mbit/s. Power over Ethernet (PoE). Product colour: White. Power consumption (max): 5 W | Vendor Homepage: https://mikrotik.com/product/lhg_5_ax#fndtn-gallery | 2.4 GHz: No | 5 GHz: Yes | Maximum data transfer rate: 1200 | Ethernet LAN data rates: 10/100/1000 | Networking standards: IEEE 802.11a/IEEE 802.11ac/IEEE 802.11ax/IEEE 802.11n | Transmitting power: 24 | Receiver sensitivity: -96, -80, -75, -70, -67 | DC-in jack: Yes | Power over Ethernet (PoE): Yes | Power over Ethernet (PoE) type supported: Passive PoE | Power consumption (max): 5 | Placement: Pole | Product colour: White | Antenna type: Internal | Antenna gain level (max): 24.5 | Built-in processor: Yes | Flash memory: 128 | Internal memory: 256 | Certification: CE, FCC, IC, EAC, ROHS | Quantity per pack: 1 | PoE adapter included: Yes | Mounting kit: Yes | Operating temperature (T-T): -40 - 70 | Unit Calculated Weight: 10.8 | Product Net Weight: 6 | Unit Calculated Volume: 0.1737 | Units per Shipping Box: 1 | Unit Width: 48 | Units per Pallet: 0 | Shipping Box Height: 47 | Unit Depth: 77 | Unit Height: 47 | Name: WRL LHG WIFI6/LHG-5AXD MIKROTIK | Model: LHG-5AXD | Model name: LHG 5 ax

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950