



Access Point MIKROTIK USB 1x10/100M RB912R-2ND- LTM



Model: RB912R-2ND-LTM

Manufacturer: MIKROTIK

EAN: 4752224000637

Product Code: 772015

R2,481

The LtAP mini is a small waterproof wireless access point with integrated LTE antennas (with two u.fl pigtails) and miniPCI-e slot, so you can use your own LTE modem of your choice.

The LtAP mini also has one 10/100 Ethernet LAN port for your wired devices. The RS232 serial port gives you console access for debugging. The unit has several powering options: 9-30 V PoE-in by Ethernet port, DC jack and microUSB.

LtAP mini has a special enclosure with with a wall mounting kit, two SIM slots to alternate between cellular providers, and integrated GPS support, making this a perfect device for use in moving vehicles like cars, buses or trains. Use the built in GPS module to track the location of your vehicle in real time, we have even provided a simple tracking application example in the RouterOS

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

documentation, to help you start development of your platform. External GPS antenna is available for ordering separately (not included, product code GPSANT).

Summary: Mikrotik LtAP mini. 2.4 GHz, Maximum data transfer rate: 54 Mbit/s, Ethernet LAN data rates: 10,100 Mbit/s. Product colour: Black. Power consumption (max): 4 W | Vendor Homepage: https://mikrotik.com/product/ltap_mini#fndtn-specifications | 2,4 GHz: Taip | 5 GHz: Ne | Didžiausias duomenų perdavimo greitis: 54 | Belaidis LAN duomenų perdavimo greitis (maks.): 54 | Eterneto LAN duomenų perdavimo norma: 10/100 | Tinklo standartai: IEEE 802.11b/IEEE 802.11g/IEEE 802.11n/IEEE 802.3af/IEEE 802.3at | Ethernet LAN (RJ-45) portų kiekis: 1 | USB jungtis: Mikro USB | WAN portas: Mobilus tinklas (SIM) | RS-232 sąsaja: Taip | AC įėjimo įtampa: 8 - 30 | Galios suvartojimas (maks.): 4 | Talpinimo: Ant stalo | Produkto spalva: Juoda | Vidinis: Ne | Antenos stiprinimo lygis (max): 1.5 | Integruotas procesorius: Taip | Flash atmintis: 16 | Vidinė atmintis: 64 | Numatyta operacinė sistema: RouterOS | Plotis: 139 | Ilgis: 77 | Aukštis: 28.5 | Darbo temperatūros diapazonas (TT): -40 - 70 | Darniosios sistemos (DS) kodas: 85176990 | Bruto svoris: 1.23 | Neto svoris: 0.35 | Vienetų skaičius vienoje siuntimo dėžėje: 20 | Vieneto plotis: 10.5 | Shipping Box Height: 25 | Vieneto gylis: 22.5 | Vieneto aukštis: 5 | Name: WRL ACCESS POINT 2.4GHZ/RB912R-2ND-LTM MIKROTIK | Model name: LtAP mini

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950