

Switch TELTONIKA TSW210000040 TSW210



Model: TSW210

Manufacturer: TELTONIKA

EAN: 4779051840243

Product Code: 772024

R2,371

The TSW210 is an unmanaged industrial switch for centralizing your resources.

Equipped with 2 SFP ports for long-range fiberoptic communication and 8 Gigabit Ethernet ports with of up to 1000 Mbps download/upload speed.

Durable, rugged aluminum housing with DIN rail and surface mounting options make the TSW210 perfect for industrial settings.

- SFP
- ETHERNET
- DURABILITY
- MOUNTING (DIN rail)

Summary: Teltonika TSW210. Switch type: Unmanaged. Basic switching RJ-45 Ethernet ports type:

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950

Gigabit Ethernet (10/100/1000), Basic switching RJ-45 Ethernet ports quantity: 8, Installed SFP modules quantity: 2. MAC address table: 2048 entries, Switching capacity: 20 Gbit/s. Networking standards: IEEE 802.3ab, IEEE 802.3ad, IEEE 802.3az, IEEE 802.3i, IEEE 802.3u, IEEE 802.3x. DC input voltage: 7 - 57 V. Wall mountable | Vendor Homepage: <https://teltonika-networks.com/product/tsw210/> | Switch type: Unmanaged | Basic switching RJ-45 Ethernet ports quantity: 8 | Basic switching RJ-45 Ethernet ports type: Gigabit Ethernet (10/100/1000) | Installed SFP modules quantity: 2 | 10G support: No | Auto MDI/MDI-X: Yes | Auto-negotiation: Yes | Networking standards: IEEE 802.3ab/IEEE 802.3ad/IEEE 802.3az/IEEE 802.3i/IEEE 802.3u/IEEE 802.3x | Jumbo frames: 9216 | Jumbo frames support: Yes | MAC address table: 2048 | Packet buffer memory: 128 | Switching capacity: 20 | DIN rail mounting: Yes | Housing material: Aluminium | International Protection (IP) code: IP30 | LED indicators: LAN/Power/Status | Product colour: Aluminium | Rack mounting: No | Stackable: No | Wall mountable: Yes | DC input voltage: 7 - 57 | Power consumption (max): 3.71 | Power consumption (typical): 1.03 | Power source: DC | Power supply included: No | Power over Ethernet (PoE): No | Operating relative humidity (H-H): 10 - 90 | Operating temperature (T-T): -40 - 75 | Depth: 95.1 | Height: 44.2 | Weight: 500 | Width: 132 | Product Net Weight: 0.5 | Shipping Box Height: 14.8 | Unit Calculated Volume: 0.001761 | Unit Calculated Weight: 0.6 | Units per Shipping Box: 1 | Model: TSW210 | Model name: TSW210000040

The product information provided is for reference purposes only. Technical specifications, photos, descriptions and prices may change without prior notice. The manufacturer and seller are not responsible for possible data discrepancies or typographical errors. We recommend checking the current information before purchasing.

shop.cssi.co.za | sales@cssi.co.za | +27 (11)541-9950